



REVISION			
LTR	DESCRIPTION	DATE	APPROVED
1	ENGINEERING RELEASE	09/13/10	V. LY



HITTITE MICROWAVE
PCB #600-00008-00-1
DRILL DRAWING

SIZE	QTY	SYM	PLATED	TOL
10	5	✕	YES	+/-3
14	167	+	YES	+/-3
63	2	□	YES	+/-3



LAYER STACKUP

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES [mm]	
DRAWING PRACTICES PER ASME Y14.100	
INTERPRET DIMENSIONS & TOLERANCES PER ASME Y14.5-2009	
TOLERANCES:	
.XX	± .01
.XXX	± .005
.XXXX	± .0020
ANGLES	± .5 DEG.

NEXT ASSY	XXXXXX
USED ON	

NOTES:

UNLESS OTHERWISE SPECIFIED:

- MATERIAL: MULTILAYER. OVERALL STACKUP AS SHOWN. TYPE ARLON 25FR OR ROGERS 4350, HALF OUNCE COPPER BOTH SIDES. FR4 TO BE USED AS FILLER TO MEET CRITICAL OVERALL THICKNESS.
- FINISH: GOLD PLATE PER ASTM B-488, TYPE III, CODE A, 8 TO 40 MICROINCHES, OVER NICKEL PER QQ-N-290, 100 MICROINCHES MINIMUM.
- PLATED THRU HOLES: .001 MINIMUM WALL THICKNESS.
- HOLE SIZES AND POSITIONS PER ARTWORK AND/OR DRILL FILE.
- ALL HOLES TO BE LOCATED WITHIN ±.003 OF THE CENTER OF THE PAD OR OTHER TRUE POSITION.
- FRONT TO BACK REGISTRATION ±.003 MAX.
- BOARD WARPAGE: <.010 PER LINEAR INCH.
- SILKSCREEN TOP SIDE ONLY WITH WHITE EPOXY INK.
- SOLDERMASK: LPI SOLDERMASK TOP SIDE. COLOR: GREEN REGISTRATION: ±.004 MAX.
- "SIZE" IN DRILL LEGEND IS IN MILS AND REFERS TO FINISHED HOLE SIZE.
- MANUFACTURE PER IPC-6012 CLASS 2.

SPECIAL REQUIREMENTS:

- CRITICAL LINE WIDTH = .016 ±.001 ON METAL-01. ADJUST PROCESS TO ACHIEVE WIDTH.
- EDGE PLATING MUST CONNECT ALL FOUR LAYERS.

VENDOR NOTES:

- VENDOR MAY ADD E-TEST STAMP TO PCB. VENDOR SHALL NOT ADD NAME, LOGO, DATE CODE, UL LISTING OR ANY OTHER MARKING TO ANY VISIBLE LAYER.
- BOARDS MUST PASS VISUAL INSPECTION PER IPC-A-600 CLASS 2.

PROPRIETARY TO HITTITE MICROWAVE CORPORATION



HITTITE MICROWAVE CORPORATION
20 Alpha Road
Chelmsford, MA 01824

TITLE

PCB, EVAL
HMC948LP3E

SIZE	CODE ID NO.	DWG NO.	REV
A	1CN88	600-00008-00	1
SCALE: 1:1		WT:	SHEET: 1 OF 1