


REVISION RECORD			
REV	DESCRIPTION	APPROVED	DATE
A	PROTO RELEASE		10-07-97



OFFHOOK	RING	OUTPUTS	VIN		REGULATION 5V to 14V
			5V	12V	
ON	OFF	VOUT1	-20.5V	-20.5V	+/- 7%
		IOUT1	60mA	60mA	
OFF	ON	VOUT2	-62V	-62V	+/- 5%
		IOUT2	35mA	60mA	

NOTES: UNLESS OTHERWISE SPECIFIED...

1. ALL RESISTOR VALUES IN OHMS, 5%, 1/10W.
2. ALL CERAMIC CAPACITORS X7R, 20%, 25V-50V.
3. LOW-ESR TANTALUM, AVX TPS-SERIES OR EQUIVALENT.
4. ELECTROLYTIC, PANASONIC VS-SERIES OR EQUIVALENT.
5. ELECTROLYTIC, SANYO CVXG-SERIES OR EQUIVALENT.

APPROVALS	DATE	LINEAR TECHNOLOGY 1630 MCCARTHY BLVD. MILPITAS, CA 95035 CORPORATION (408) 452-1900		
		SCHEMATIC: DESCRIPTION SLIC POWER, -20.5V, -62V		
	SIZE B	DOCUMENT NUMBER DC161A	REV A	
				SHEET 1 OF 1