330a-RO.pcb - Thu Oct 19 14:29:04 2000

REVISIONS			
REV		APPR	DATE

NOTES: Unless Otherwise Specified

1. MATERIAL: 2 LAYERS, 0.062" THK. FR-4 GLASS EPOXY 2 OZ. COPPER CLAD.
2. ALL HOLE SHALL BE PLATED TRHU.
3. PLATE THRU HOLES WITH COPPER .0014 MIN. THICKNESS. ALL HOLE SIZES IN HOLE TABLE ARE AFTER PLATING.
4. SILKSCREEN: WITH WHITE EPOXY NON-CONDUCTIVE INK.
5. NO SILKSCREEN ALLOWED ON PADS LANDS.
6. SOLDER MASK: LPI, GREEN.
7. NO BLOCK SOLDERMASKING OF PADS ROWS.
8. DO NOT MAKES CHANGES ON SILKSCREEN, SUCH AS COMPANY LOGO, QC STAMPS.
9. DO NOT PLATE TOOLING(3PLCS) AND SCORING(26PLCS) HOLES. (Reference Drawing Dwg No. DC205A)
10. SCORING:



Linear Tech. Corp.
Demo Board 330A
LT1761



SIZE	QTY	SYM	PLTD
10	8	+	PLTD
35	2	X	PLTD
70	2	□	NPLTD
61	8	◇	PLTD

Fabrication Drawing

APPROVALS		
	INIT	DATE
DRAWN		
CHECK		
DESIGN	RmB	
ENGR		
SCALE = NONE		

LINEAR TECHNOLOGY
1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: 100mA Low Noise LDO Regulator

SIZE		REV.
NONE	Demo Board 330	A
DES-xxxxxx		SHT 1 of 1