


REV 3		REV 3		REV 3	
ECO	REV	DESCRIPTION	DATE	APPROVED	
	3	RELEASE	10/31/02		

REVISION HISTORY

NOTES: UNLESS OTHERWISE SPECIFIED,

1. ARTWORK P/N DC519A REV 3.
2. FAB PER IPC-A-600
3. MATERIAL: EPOXY FIBERGLASS, NEVA GRADE FR-4, 2007 +/- .005 INCH THICKNESS WITH 2 OZ. COPPER ON BOTH SURFACES AND 1 OZ. COPPER ON TWO INTERNAL LAYERS. FLAMABILITY RATING #1-V-2 MINIMUM.
4. SIZE CUT TO DIMENSIONS AND TOLERANCES SHOWN. 0.00 ARE PRIMARY DATUMS.
5. BOARD: SELECTIVE PLATED BOARD, SOLDER MASK OVER BARE COPPER, COLORED GREEN LIP, SOLDEREN COMPONENT SIDE WITH TELLUR NON-SOLDEREN COMPONENT SIDE.
6. DRILL: ALL HOLES SHALL BE DRILLED +/- .003 INCH MIN. PLATING THICKNESS: 1 OZ. EXCEPT WHERE PLATING NOT REQUIRED.
7. DROP: ALL UNUSED PADS ON INNER LAYERS.
8. DO NOT ALTER ARTWORK 6.0, TO ADD LOGO OR DATE CODE.




HOLE LEGEND

TOLERANCE	SIZE	QTY	SYM	RLTD
+/-0.003		10	+	RLTD
+/-0.003		20	53	RLTD
+/-0.005		70	2	NPLTD
+/-0.01		84	20	RLTD

L1 - COMPONENT SIDE

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE .31°
2 PLACE ±.01 3 PLACE ±.005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

THIRD ANGLE PROJECTION



DO NOT SCALE DRAWING

CONTRACT NO

APPROVALS	DATE
DRAWN	08/27/02
CHECKED	
APPROVED	
ENGINEER	

TITLE

FAB, LT1940EFE 1.1MHz DUAL STEP-DOWN
DC/DC CONVERTER

SIZE	CAGE CODE	DWG NO	REV
B		DC519A	3
SCALE		1/1	1 OF 1
2		FLEMING 516A-3.163	SHEET 1 OF 1