REVISIONS			
REV	DESCRIPTION	APPR	DATE



NOTES: Unless Otherwise Specified:

1. PCBS Are To Be RoHS Compliant
2. Fab Per IPC-A-600
3. Material: Epoxy Fiberglass, NEMA Grade FR-4, 4 Layers
   .062 +/- .005 Inch Thickness With
   2 OZ. Copper Finished On All Outer Layers,
   1 OZ. Copper On All Internal Layers.
   Flammability Rating: 94 V-2 Minimum.
4. Size: Cut To Dimensions And Tolerances Shown.
   0.00 Are Primary Datums.
5. Finish: SMOBC Using Wet Mask, Or LPI Both Sides, Green Preferrable.
   Silkscreen Component Side With White Non-conductive Ink.
   Gold Immersion Both Sides (Not Required For Prototype Boards)
6. Drilling: Drill Holes Per Schedule. Plate Through
   Holes With Copper, .001 Inch Thick Min. All
   Hold Sizes Are Specified After Plating.
   Holes Location Tolerances Are +/-.003" In Relation To Center.
7. Do Not Alter Artwork To Add Logo Or Date Code,
   But You May Modify Pad Size To Meet End Finish.
8. Scoring: (Not Required For Prototype Boards)



SIZE	QTY	SYM	PLTD	TOL
72	2	X	NO	+/-0.0
40	15	⊓	YES	+/-0.0
15	18	◇	YES	+/-0.0
95	4	⧖	YES	+/-0.0

Fabrication Drawing

APPROVALS		
	INIT	DATE
DRAWN	KL	
CHECK		
DESIGN		
ENGR	KH	
SCALE = NONE		

LINEAR TECHNOLOGY
1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

LT1965EDD
1.1A Low Dropout Regulator

SIZE	DEMO BRD	REV.
	DC1172A	A

SHT 1 of 1