




1. FAB PER IPC-A-600
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4
 - FINISHED THICKNESS TO BE 0.062" +/- .005"
 - TOTAL OF 6 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.
 - FLAMMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00" ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001" THICK MIN.
ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/-0.003"
IN RELATION TO CENTER
5. FINISH: -SMOBC USING LPT BOTH SIDES, COLOR GREEN.
-GOLD IMMERSION BOTH SIDES.
-FOR SILKSREEN: BOTH SIDES USE WHITE NON-CONDUCTIVE INK.
6. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
7. PCBs ARE TO BE RoHS COMPLIANT.
8. SCORING FOR PANELIZED PCBs:



SIZE	QTY	SYM	PLATED	TOL
31	15	+	YES	+/-3Mil
70	2	×	NO	+/-3Mil
10	29	◇	YES	+/-3Mil
94	9	⊗	YES	+/-3Mil

<div>UNLESS OTHERWISE SPECIFIED</div> <div>DIMENSIONS ARE IN INCHES</div> <div>TOLERANCES: 0.XX" = ± 0.01" 0.XXX" = ± 0.005"</div> <div>INTERPRET DIM AND TOL PER ASME Y14.5M-1994</div> <div>THIRD ANGLE PROJECTION</div> <div></div>	APPROVALS		<div></div> <div>16500 MCCARTHY BLVD FARMERS BRANCH, TX 75445 PH: (409) 432-1900 WWW.LINEAR.COM LITC CONFIDENTIAL - FOR CUSTOMER USE ONLY</div>			
	PCB DES.	R8				
	APP ENG.	MOLLY Z.				
SCALE = NONE	SIZE	IC NO.	LT3071EUFD	REV	1	
	N/A		DEMO CIRCUIT 1434A			
	FILENAME:		DC1434A-1.PCB		SHT 1 OF 1	