

# LT3072

## Dual, Low Noise, 2.5A Programmable Output, Low Dropout Linear Regulator

### DESCRIPTION

Demonstration Circuit 1938A features the [LT3072](#) dual, low noise, 2.5A programmable output, low dropout linear regulator. The input voltages  $V_{IN1}$  and  $V_{IN2}$  are independent and can range from 0.8V to 3.45V. Each channel has jumpers to set a three-bit code that determines output voltages  $V_{OUT1}$  and  $V_{OUT2}$  at pre-programmed levels with a range from 0.6V to 2.5V and a maximum output current of 2.5A. DC1938A requires a single external BIAS voltage that is higher than  $V_{IN1}$  and  $V_{IN2}$ , between 2.375V and 5.25V and is at least 1.2V higher than the highest output voltage.

Each output is decoupled by a  $1\mu\text{F} + 2.2\mu\text{F} + 6.8\mu\text{F}$  capacitor network and each input is decoupled with a  $22\mu\text{F}$  capacitor. The internal reference of each channel is bypassed with a  $0.1\mu\text{F}$  capacitor to reduce output noise and program the soft-start.  $1500\mu\text{F}$  aluminum electrolytic capacitors and  $220\mu\text{F}$  tantalum polymer capacitors hold up  $V_{IN1}$  and  $V_{IN2}$  but the aluminum electrolytic capacitors are cabling dependent and are not required on customer circuits. The BIAS voltage is bypassed at each channel's BIAS pin with a  $2.2\mu\text{F}$  capacitor and there is a single terminal for the BIAS input.

The positions of the  $V_{OUT1}$  and  $V_{OUT2}$  ENABLE jumpers either pull up the EN1 and EN2 pins to the BIAS voltage by a  $100\text{k}\Omega$  resistor, short EN1 and EN2 to ground or float EN1 and EN2 so they can be driven directly by a signal applied to the EN1 and EN2 terminals. Each channel has a terminal for PWRGD that is pulled up to BIAS by a  $51\text{k}\Omega$  resistor. Resistors program a 3A output current limit and a  $333\text{mV/A}$  output current monitoring voltage that is available at the IMON/LIM terminals. The TEMP terminal allows monitoring of die temperature.

VOIC allows automatic control of a pre-regulation voltage and the VOIC pins are bypassed with  $1\text{nF}$  capacitors. MARGA1 and MARGA2 terminals for margining allow an optional external voltage to program an adjustment to each channel's output voltage.

Banana jacks minimize voltage drops on VIN and VOUT connections. Each channel's SENSE pin terminates at a  $10\mu\text{F}$  capacitor near the VOUT banana jacks. The PCB design minimizes parasitic SENSE to GND and SENSE to OUT trace capacitance.  $VO1+$ ,  $VO1-$ ,  $VO2+$  and  $VO2-$  terminals Kelvin-connect to the  $10\mu\text{F}$  VOUT capacitors and are the optimal place to observe output voltage regulation and load transient response. Each output has a  $560\Omega$  pre-load so the minimum load requirement is met over the VOUT programming range.

DC1938A has placeholders identified on the schematic as optional (Opt) components that make it convenient to add capacitance, add filtering, parallel references or use the VOIC function – check the schematic for placeholder locations.

The LT3072 is well suited to microprocessor systems and instrumentation applications with stringent performance requirements for output noise and load transient response. Systems with high efficiency requirements will benefit from the low dropout of the LT3072. DC1938A features the LT3072 in a thermally enhanced 36-lead  $4\text{mm} \times 7\text{mm}$  QFN package. The LT3072 data sheet must be read in conjunction with this demo manual to properly use or modify demo circuit DC1938A.

**[Design files for this circuit board are available.](#)**

All registered trademarks and trademarks are the property of their respective owners.

## PERFORMANCE SUMMARY Specifications are at $T_A = 25^\circ\text{C}$

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
Minimum Input Voltage, $V_{IN1}$ or $V_{IN2}$				0.8	V
Maximum Input Voltage, $V_{IN1}$ or $V_{IN2}$		3.45			V
Minimum Bias Voltage, $V_{BIAS}$	$V_{BIAS} > V_{IN1}$ , $V_{BIAS} > V_{IN2}$ , $V_{BIAS} \geq V_{OUT1} + 1.2\text{V}$ , and $V_{BIAS} \geq V_{OUT2} + 1.2\text{V}$			2.375	V
Maximum Bias Voltage, $V_{BIAS}$		5.25			V
Output Voltage, $V_{OUT1}$ or $V_{OUT2}$	$V_{OUT} = 0.6\text{V}$ , $10\text{mA} \leq I_{OUT} \leq 2.5\text{A}$ , $0.90\text{V} \leq V_{IN} \leq 1.05\text{V}$	0.59		0.61	V
	$V_{OUT} = 1.0\text{V}$ , $10\text{mA} \leq I_{OUT} \leq 2.5\text{A}$ , $1.3\text{V} \leq V_{IN} \leq 1.45\text{V}$	0.98		1.02	V
	$V_{OUT} = 1.2\text{V}$ , $10\text{mA} \leq I_{OUT} \leq 2.5\text{A}$ , $1.5\text{V} \leq V_{IN} \leq 1.65\text{V}$	1.18		1.22	V
	$V_{OUT} = 1.5\text{V}$ , $10\text{mA} \leq I_{OUT} \leq 2.5\text{A}$ , $1.8\text{V} \leq V_{IN} \leq 1.95\text{V}$	1.48		1.52	V
	$V_{OUT} = 1.8\text{V}$ , $10\text{mA} \leq I_{OUT} \leq 2.5\text{A}$ , $2.1\text{V} \leq V_{IN} \leq 2.25\text{V}$	1.77		1.83	V
	$V_{OUT} = 2.5\text{V}$ , $10\text{mA} \leq I_{OUT} \leq 2.5\text{A}$ , $2.8\text{V} \leq V_{IN} \leq 2.95\text{V}$	2.46		2.54	V
Maximum Output Current, $I_{OUT1}$ or $I_{OUT2}$		2.5			A
Output Current Limit, $I_{OUT1}$ or $I_{OUT2}$	$R1 = R2 = 1\text{k}\Omega$		3		A

## QUICK START PROCEDURE

To use DC1938A to evaluate the performance of the LT3072, refer to Figure 1 for the proper equipment setup and follow the procedure below:

1. With the input supplies and loads off and turned down, make all connections according to Figure 1. Make sure the jumpers to set  $V_{OUT1}$  and  $V_{OUT2}$  are in the proper positions for the desired output voltage according to Table 1 of the LT3072 data sheet. Make sure the  $V_{OUT1}$  ENABLE and  $V_{OUT2}$  ENABLE jumpers are in the ON position.
2. Turn on the input and bias supplies and increase them to the desired voltages. The BIAS voltage must be higher than  $V_{IN1}$  and  $V_{IN2}$ , between 2.375V and 5.25V and at least 1.2V higher than the highest output voltage.

**NOTE: WHEN SETTING THE INPUT AND BIAS VOLTAGES:** An input or bias voltage that is too close to the programmed output voltage (too low) may cause dropout operation and a loss of output voltage regulation. Also, an input voltage that is too high above the output may increase power dissipation to an unacceptable level.

3. Increase the load to the desired output current. Verify that  $V_{OUT1}$  and  $V_{OUT2}$  are as programmed by the jumpers.

**NOTE:** If the output voltage is low, temporarily disconnect the load to make sure that it is not set too high.

4. Once the proper output voltages are established, adjust the input voltages and loads within the operating ranges and observe the output voltage regulation, load transient response and other parameters.

## QUICK START PROCEDURE




Figure 1. Proper Equipment Setup for DC1938A.





Figure 2. Thermal Image with 3.1V<sub>IN1</sub>, 3.1V<sub>IN2</sub>, 2.5V<sub>OUT1</sub> at 2.5A and 2.5V<sub>OUT2</sub> at 2.5A. Vertical Orientation with No Forced Air.

# DEMO MANUAL DC1938A

## PARTS LIST

ITEM	QTY	REFERENCE	PART DESCRIPTION	MANUFACTURER/PART NUMBER
<b>Required Circuit Components</b>				
1	2	C1, C2	Cap., X5R, 2.2μF, 10V, 20%, 0603	Taiyo Yuden LMK107BJ225MA-T
2	2	C3, C4	Cap., X5R, 0.1μF, 25V, 10%, 0402	AVX, 04023D104KAT2A
3	2	C5, C7	Cap., X5R, 2.2μF, 10V, 20%, 0805	AVX, 0805ZD225MAT2A
4	2	C6, C8	Cap., X7R, 1.0μF, 25V, 10%, 0805	AVX, 08053C105KAT2A
5	2	C9, C10	Cap., X5R, 22μF, 6.3V, 20%, 0805	TDK C2012X5R0J226M
6	2	C13, C17	Cap., X7R, 1000pF, 25V, 20%, 0402	AVX 04023C102MAT2A
7	2	C20, C21	Cap., X5R, 6.8μF, 6.3V, 10%, 0805	AVX, 08056D685KAT2A
8	2	C24, C25	Cap., Tant. Polymer 220μF, 6.3V, 20%, 7343	AVX TCJY227M006R0025
9	2	R1, R2	Res., Chip 1.00k, 0.06W, 1%, 0603	Vishay CRCW06031K00FKEA
10	2	R10, R11	Res., Chip 560, 0.06W, 5%, 0603	Vishay CRCW0603560RJNEA
11	1	U1	I.C., LDO Reg. QFN-UFF-36-4X7-1863-RV0	Analog Devices., LT3072EUFF#PBF
<b>Optional Demo Circuit Components</b>				
1	0	C11, C12 (Opt)	Cap., 0603	
2	0	C14, C15, C16, C18, C19, C30, C31 (Opt)	Cap., 0402	
3	0	C22, C23 (Opt)	Cap., 1206	
4	2	C26, C27	Cap., X5R, 10μF, 10V, 10%, 0805	AVX 0805ZD106KAT2A
5	2	C28, C29	Cap., Al Elect. 1500μF, 6.3V, 20%, 10mm/DIA	Panasonic EEEFK0J152P
6	2	R3, R4	Res., Chip 51k, 0.06W, 5%, 0603	Vishay CRCW060351K0JNEA
7	0	R5, R6, R9, R12, R13 (Opt)	Res., 0603	
8	2	R7, R8	Res., Chip 100k, 0.06W, 5%, 0603	Vishay CRCW0603100KJNEA
<b>Hardware</b>				
1	16	E1, E2, E3, E4, E9, E10, E11, E12, E13, E14, E15, E16, E21, E22, E23, E24	Turret, Testpoint 0.063"	Mill Max 2308-2-00-80-00-00-07-0
2	8	E5, E6, E7, E8, E17, E18, E19, E20	Connector, Banana Jack	Keystone 575-4
3	4	E26, E27, E28, E29	Testpoint, Turret, .094" pbf	Mill-Max, 2501-2-00-80-00-00-07-0
4	8	JP1, JP2, JP3, JP4, JP5, JP6, JP7, JP8	Headers, 4 Pins 2mm Ctrs.	Sullin, NRPN041PAEN-RC
5	8	XJP1, XJP2, XJP3, XJP4, XJP5, XJP6, XJP7, XJP8	Shunt, 2mm Ctrs.	Samtec 2SN-BK-G
6	4	MH1-MH4	Standoff, Nylon, 0.5, 1/2" SNAP ON	Keystone, 8833

## SCHEMATIC DIAGRAM



# DEMO MANUAL DC1938A

---



## ESD Caution

**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

## Legal Terms and Conditions

By using the evaluation board discussed herein (together with any tools, components documentation or support materials, the "Evaluation Board"), you are agreeing to be bound by the terms and conditions set forth below ("Agreement") unless you have purchased the Evaluation Board, in which case the Analog Devices Standard Terms and Conditions of Sale shall govern. Do not use the Evaluation Board until you have read and agreed to the Agreement. Your use of the Evaluation Board shall signify your acceptance of the Agreement. This Agreement is made by and between you ("Customer") and Analog Devices, Inc. ("ADI"), with its principal place of business at One Technology Way, Norwood, MA 02062, USA. Subject to the terms and conditions of the Agreement, ADI hereby grants to Customer a free, limited, personal, temporary, non-exclusive, non-sublicensable, non-transferable license to use the Evaluation Board FOR EVALUATION PURPOSES ONLY. Customer understands and agrees that the Evaluation Board is provided for the sole and exclusive purpose referenced above, and agrees not to use the Evaluation Board for any other purpose. Furthermore, the license granted is expressly made subject to the following additional limitations: Customer shall not (i) rent, lease, display, sell, transfer, assign, sublicense, or distribute the Evaluation Board; and (ii) permit any Third Party to access the Evaluation Board. As used herein, the term "Third Party" includes any entity other than ADI, Customer, their employees, affiliates and in-house consultants. The Evaluation Board is NOT sold to Customer; all rights not expressly granted herein, including ownership of the Evaluation Board, are reserved by ADI. CONFIDENTIALITY. This Agreement and the Evaluation Board shall all be considered the confidential and proprietary information of ADI. Customer may not disclose or transfer any portion of the Evaluation Board to any other party for any reason. Upon discontinuation of use of the Evaluation Board or termination of this Agreement, Customer agrees to promptly return the Evaluation Board to ADI. ADDITIONAL RESTRICTIONS. Customer may not disassemble, decompile or reverse engineer chips on the Evaluation Board. Customer shall inform ADI of any occurred damages or any modifications or alterations it makes to the Evaluation Board, including but not limited to soldering or any other activity that affects the material content of the Evaluation Board. Modifications to the Evaluation Board must comply with applicable law, including but not limited to the RoHS Directive. TERMINATION. ADI may terminate this Agreement at any time upon giving written notice to Customer. Customer agrees to return to ADI the Evaluation Board at that time. LIMITATION OF LIABILITY. THE EVALUATION BOARD PROVIDED HEREUNDER IS PROVIDED "AS IS" AND ADI MAKES NO WARRANTIES OR REPRESENTATIONS OF ANY KIND WITH RESPECT TO IT. ADI SPECIFICALLY DISCLAIMS ANY REPRESENTATIONS, ENDORSEMENTS, GUARANTEES, OR WARRANTIES, EXPRESS OR IMPLIED, RELATED TO THE EVALUATION BOARD INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, TITLE, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. IN NO EVENT WILL ADI AND ITS LICENSORS BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES RESULTING FROM CUSTOMER'S POSSESSION OR USE OF THE EVALUATION BOARD, INCLUDING BUT NOT LIMITED TO LOST PROFITS, DELAY COSTS, LABOR COSTS OR LOSS OF GOODWILL. ADI'S TOTAL LIABILITY FROM ANY AND ALL CAUSES SHALL BE LIMITED TO THE AMOUNT OF ONE HUNDRED US DOLLARS (\$100.00). EXPORT. Customer agrees that it will not directly or indirectly export the Evaluation Board to another country, and that it will comply with all applicable United States federal laws and regulations relating to exports. GOVERNING LAW. This Agreement shall be governed by and construed in accordance with the substantive laws of the Commonwealth of Massachusetts (excluding conflict of law rules). Any legal action regarding this Agreement will be heard in the state or federal courts having jurisdiction in Suffolk County, Massachusetts, and Customer hereby submits to the personal jurisdiction and venue of such courts. The United Nations Convention on Contracts for the International Sale of Goods shall not apply to this Agreement and is expressly disclaimed.

Rev. 0