


- ART01 = LAYER 1 (COMPONENT SIDE)
- ART02 = LAYER 2 (GND)
- ART03 = LAYER 3 (SIGNAL)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES : Unless Otherwise Specified

- 1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
THICKNESS .062 +/--.006 TOTAL OF 4 LAYERS
- 2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
ELECTRODEPOSITED TIN-LEAD COMPOSITION
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC)
- 3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT
- 4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
- 5. ALL DIMENSIONS ARE IN INCHES
- 6. SCORING:



SIZE	QTY	SYM	PLTD
15	19	V	PLTD
80	4	W	PLTD
35	6	X	PLTD
72	2	Y	NPLTD
95	6	Z	PLTD

Fabrication Drawing

APPROVALS		LINEAR TECHNOLOGY		1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE			
CHECK					
DESIGN					
ENGR					
TITLE: Single Cell White LED Driver LT3465ES6/LT3465AES6					
SIZE	A	DC637	REV. A		
SCALE = NONE			DES- SHT 1 of 1		