



REVISIONS		
REV	DESCRIPTION	APPR DATE



Component Side

NOTES : Unless Otherwise Specified


1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.  
2 OZ. COPPER FINISH ON OUTER LAYERS.  
1 OZ. COPPER FINISH ON INNER LAYERS.  
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS.  
FLAMABILITY RATING: 94 V-0 MINIMUM .  
0.000 ARE PRIMARY DATUMS.
3. SIZE: DIMENSIONS AND TOLERANCES SHOWN.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH  
HOLES WITH COPPER, .001 INCH THICK MIN. ALL  
HOLE SIZES ARE SPECIFIED AFTER PLATING.  
HOLE LOCATION TOLERANCES ARE +/- .003  
INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.  
IMMERSION GOLD SOLDER PLATING
6. SILKSCREEN : BOTH SIDES USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
8. SCORING:



Fabrication Drawing

SIZE	QTY	SYM	PLTD	TOL
0.07	2	□	NO	+/-0.003
0.095	4	◇	YES	+/-0.003
0.01	148	⊗	YES	+/-0.003
0.035	15	⊕	YES	+/-0.003
0.065	18	+	YES	+/-0.003

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES ON ANGLE ± 1  
2 PLACE ± .01 3 PLACE ± .005  
INTERPRET DIM AND TOL  
PER ASME Y14.5M - 1994

APPROVALS			 LINEAR TECHNOLOGY		1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
	INIT	DATE	TITLE: LT3496EUF			
DRAWN			Triple Boost or Buck/Boost LED Driver			
CHECK			SIZE A DEMO DC1288A REV. A			
DESIGN	Helen	4/03/07	SHT 1 of 1			
ENGR	Walker Big	4/03/07	DES-250			
SCALE = NONE			DES-250			