


- LAYER 1 (COMPONENT SIDE)
- LAYER 2 (GND)
- LAYER 3 (GND)
- LAYER 4 (SOLDER SIDE)

NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY
2 OZ OUTER, 1 OZ INNER COPPER CLAD
THICKNESS .062 +/--.006 TOTAL OF 4 LAYERS
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
WHITE TIN IMMERSION (OMIKRON) BOTH SIDES,
OR LEAD FREE SOLDER
3. SOLDER MASK : BOTH SIDES USING GREEN LPI OR EQUIVALENT
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
5. DO NOT ALTER ARTWORK e.g. TO ADD LOGO, DATE, OR TEST CODE.
6. ALL DIMENSIONS ARE IN INCHES
7. SCORING:



Fabrication Drawing

SIZE	QTY	SYM	PLTD	TOL
20	44	X	YES	+/-0.003
95	14	□	YES	+/-0.003
10	21	◇	YES	+/-0.003
13	22	⊗	YES	+/-0.003
34	3	⊗	YES	+/-0.003
70	2	⊕	NO	+/-0.0

APPROVALS		INIT		DATE	
DRAWN					
CHECK					
DESIGN	Antonina K				
ENGR	Tiger Zhou				
SCALE = NONE		DES-		SHT 1 of 1	

TITLE: LT3501EFE	
DUAL MONOLITHIC STEP-DOWN DC/DC CONVERTER	
SIZE	A
DEMO CIRCUIT	964A
Rev	4

1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900