



REVISIONS		
REV	DESCRIPTION	DATE

NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.  
2 OZ. COPPER FINISH ON OUTER LAYERS.  
1 OZ. COPPER FINISH ON INNER LAYERS.  
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS.  
FLAMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: DIMENSIONS AND TOLERANCES SHOWN.  
0.00 ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER. .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.  
HOLE LOCATION TOLERANCES ARE +/- .003 INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.  
SILVER IMMERSON BOTH SIDES.
6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
8. SCORING:



SIZE	QTY	SYM	PLTD
95	5	+	PLTD
35	3	X	PLTD
10	10	□	PLTD
70	2	◇	NPLTD

FAB DRAWING

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES ON ANGLE ±1  
2 PLACE ±.01 3 PLACE ±.005  
INTERPRET DIM AND TOL  
PER ASME Y14.5M - 1994

APPROVALS		DATE	
DRAWN		INIT	
CHECK			
DESIGN	J. WU	4/19/07	
ENGR	M. Zhu	4/19/07	
SCALE = NONE			

LINEAR TECHNOLOGY

1630 McCarthy Blvd.  
Milpitas, CA 95035  
PH: (408)432-1900

TITLE:

LT3502EDC

40V, 500mA, 1.1MHz Buck Regulator in 2x2 DFN

SIZE

A

DC1221A

REV. A

SHT 1 of 1