



REVISIONS		
REV	DESCRIPTION	DATE



**NOTES : Unless Otherwise Specified**

1. FAB PER IPC-A-600
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4  
FINISHED THICKNESS TO BE 0.062" +/- 0.006"  
TOTAL OF 4 LAYERS WITH 2 OZ. COPPER ON THE OUTER LAYERS AND 1 OZ. COPPER ON THE INTERNAL LAYERS.  
FLAMABILITY RATING: 94 V-0 MINIMUM .
3. FINISH: SMOBC USING LPI BOTH SIDES, COLOR GREEN.  
WHITE TIN IMMERSION (OWIKRON). ( not required for prototype )  
FOR SILKSCREEN: USE WHITE NON-CONDUCTIVE INK.
4. DRILLING: DRILL HOLES PER SCHEDULE. ALL PLATED THROUGH HOLES WITH COPPER, 0.001" MIN. / 0.0015" MAX. COPPER PLATE  
ALL HOLE SIZES ARE SPECIFIED AFTER PLATING. HOLE LOCATION TOLERANCES ARE +/-0.003" IN RELATION TO CENTER
5. ALL DIMENSIONS ARE IN INCHES
6. SCORING FOR PANELIZED PCB: ( not required for prototype )



SIZE	QTY	SYM	PLTD
72	2	X	NPLTD
95	12	□	PLTD
10	60	◇	PLTD

# Fabrication Drawing

<div>APPROVALS</div>			<div><div><div><div></div><div>LINEAR</div><div>TECHNOLOGY</div></div><div><div>1630 McCarthy Blvd.</div><div>Milpitas, CA 95035</div><div>PH: (408)432-1900</div></div></div></div>			<div><div>LT3518EUF</div><div>Full-Featured LED Driver with 2.3A Switch Current</div></div>		
<div><div>DRAWN</div><div>CHECK</div><div>DESIGN</div><div>ENGR</div></div>			<div><div>SIZE</div><div>A</div></div>		<div><div>DC1160A</div><div>REV.</div></div>			
<div><div>SCALE = NONE</div></div>			<div>SHT 1 of 1</div>					