


SHOWN FROM COMPONENT SIDE


REVISIONS			
REV	DESCRIPTION	APPR	DATE
A	PROTOTYPE RELEASE		

SIZE	QTY	SYM	PLTD	TOL
0.07	2	+	NO	+/-0.003"
0.125	4	×	YES	+/-0.003"
0.035	6	□	YES	+/-0.003"
0.015	37	◇	YES	+/-0.003"
0.094	6	⊗	YES	+/-0.003"
0.12	2	⊗	YES	+/-0.003"

#### NOTES: UNLESS OTHERWISE SPECIFIED

- FAB PER IPC-A-600
- MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4  
 FINISHED THICKNESS TO BE 0.062" +/- 0.006"  
 TOTAL OF 4 LAYERS WITH 2 OZ. COPPER ON THE OUTER LAYERS AND 1 OZ. COPPER ON THE INTERNAL LAYERS.  
 FLAMABILITY RATING: 94 V-0 MINIMUM .
- FINISH: SMOBC USING LPI BOTH SIDES, COLOR GREEN.  
 SILVER IMMERSION (OMIKRON).  
 FOR SILKSCREEN: USE WHITE NON-CONDUCTIVE INK.
- DRILLING: DRILL HOLES PER SCHEDULE. ALL PLATED THROUGH HOLES WITH COPPER, 0.001" MIN. / 0.0015" MAX. COPPER PLATE  
 ALL HOLE SIZES ARE SPECIFIED AFTER PLATING. HOLE LOCATION TOLERANCES ARE +/-0.01" IN RELATION TO CENTER
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
- SCORING FOR PANELIZED PCB:



APPROVALS			 <b>LINEAR TECHNOLOGY</b>		1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
	INIT	DATE				
DRAWN			TITLE: FABRICATION DRAWING <b>HIGH CURRENT CAPACITIVE CHARGING CIRCUIT</b>			
CHECK						
DESIGN	KIM T.	06-22-05				
ENGR	DAVID NG	06-22-05				
			SIZE	DEMO	REV.	
			A	DC891A-1 * LT3750EMS	A	
SCALE = NONE			DES- 0000		SHT 1 of 1	