



REVISION HISTORY				
ECO	REV	DESCRIPTION	APP. ENG.	DATE
-	5	PRODUCTION	KEITH S.	11-15-13



NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
5. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.

APPROVALS		 <div> 1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 www.linear.com LTC CONFIDENTIAL— FOR CUSTOMER USE ONLY </div>	
PCB DES.	LT		
APP ENG.	KEITH S.	TITLE: TOP ASSEMBLY DRAWING	
		TRIPLE LED BOOST CONTROLLER	
		SIZE	IC NO.
		N/A	LT3797EUKG
			REV. 5
SCALE = NONE		FILENAME: DC1784A-5.PCB	
		SHT 1 OF 1	