


SIZE	QTY	SYM	PLTD
35	5	W	PLTD
10	279	X	PLTD
120	2	Y	PLTD
95	6	Z	PLTD



NOTES: UNLESS OTHERWISE SPECIFIED

1. FAB PER IPC-A-600
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4
FINISHED THICKNESS TO BE .062 +/- .005 INCH
WITH 2 OZ. COPPER ON TWO OUTER LAYERS AND
1 OZ. COPPER ON TWO INTERNAL LAYERS.
FLAMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
HOLES WITH COPPER, .001 INCH THICK MIN. ALL
HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/- .003
INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING WET MASK, OR LPI BOTH SIDES, GREEN
PREFERRABLE. SILKSCREEN COMPONENT SIDE WITH
WHITE NON-CONDUCTIVE INK.
6. CONTROLLED 50 OHM IMPEDANCE (AT 2.5 GHz FREQ.) FOR
LAYER 1-2 AND LAYER 4-3.
- ⑦ SUBJECT TO CHANGE BY MANUFACTURER, DEPENDING ON DIELECTRIC
CONSTANT DEVIATIONS. PLEASE CONSULT LTC.
8. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
9. WHEN PANELIZED THIS BOARD. PLEASE MERGE TEST BOARD TOGETHER.
THE TEST BOARD NEED TO BE BUILT IN THE SAME PANEL. MIN. BUILD
ONE TEST BOARD EACH PANEL.

FAB DRAWING