


REVISIONS			
REV	DESCRIPTION	APPR	DATE

**NOTES: UNLESS OTHERWISE SPECIFIED.**


- ARTWORK P/N Demo Circuit 1114A Rev1
- FAB PER IPC-A-600, 2 Layers.
- MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4 .062 +/- .005 INCH THICKNESS WITH 2 OZ. COPPER FINISH AND FLAMABILITY RATING: 94 V-2 MINIMUM.

- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN. 0.00 ARE PRIMARY DATUMS.
- BOARD: SELECTIVE PLATED BOARD. SOLDER MASK OVER BARE COPPER, COLOR, GREEN LPI, WHITE TIN IMMERSION (OMIKRON) BOTH SIDES. SILKSCREEN BOTH SIDES WITH WHITE NON-CONDUCTIVE INK.
- PLATE THRU ALL HOLES WITH COPPER MIN. PLATING THICKNESS: 1 OZ. EXCEPT WHERE PLATING NOT REQUIRED
- DRILL: ALL HOLES SHALL BE DRILLED +.03mil WITH RESPECT TO CTR. OF DRILLED PAD. ALL HOLES FINISHED SIZE AFTER PLATING.
- DROP ALL UNUSED PADS ON INNER LAYERS.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
- SCORING:




**FAB DRAWING**

**Demo Circuit 1114A**  
**FAB DRAWING**



SIZE	QTY	SYM	PLATED	TOL
70	2	✕	NO	+/- .3mil
63	5	□	YES	+/- .3mil
31	12	◇	YES	+/- .3mil

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES ON ANGLE 1+  
3 PLACE .005+  
INTERPRET DIM AND TOL  
PER ASME Y14.5M - 1994

APPROVALS				<div>  <div> 1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900 </div> </div>			
DRAWN	INT	DATE					
CHECK				TITLE:			
DESIGN	Rud98	03/04/08		Over-The-Top Current Sense Amplifier			
ENGR	JoniL	03/04/08					
SCALE = NONE				SIZE	A	Demo Circuit 1114A	REV. 1
				SHT 1 of 1			