



REVISION HISTORY			
ECO	REV	DESCRIPTION	APPR
-	4	PRODUCTION	V.K. 11-21-18



NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. MAXIMUM SOLDER TEMPERATURE IS 240 DEG C.
3. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD.
4. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS.
5. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER.
6. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
7. INSTALL STANOFFS AS SHOWN ON ASSY DRAWING.
8. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
9. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
10. INSTALL 4 STANOFFS AT LOCATIONS AS SHOWN BELOW:



11. WRITE APPROPRIATE ASSEMBLY VERSION WITH BLACK PERMANENT MARKER AS SHOWN IN TABLE BELOW:

ASSEMBLY VERSION	
DC2332A-A	<input checked="" type="checkbox"/> MASTER <input type="checkbox"/> SLAVE
DC2332A-B	<input type="checkbox"/> MASTER <input checked="" type="checkbox"/> SLAVE

ANALOG | **POWER BY LINEAR**™ www.analog.com
FOR ADI CUSTOMER USE ONLY

TITLE: TOP ASSEMBLY DRAWING
MULTIPHASE BOOST CONVERTER
EXPANDER WITH INTERNAL GATE DRIVERS

SIZE IC NO. LT8551EUKG
N/A DC2332A REV. 4

FILENAME: DC2332A-4.PCB SHT 1 OF 2