

NOTES: UNLESS OTHERWISE SPECIFIED...

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-600E.
2. ALL DIMENSIONS ARE IN INCHES, $\pm .003$.
FINISHED HOLE SIZES ARE $+.003/-0$.
3. FINISHED MATERIAL IS FR4, .062-THICK, 2-oz Cu, 2-LAYERS.
PLATED HOLE WALL THICKNESS .001 MIN.
PANEL OUTLINE DIMENSIONS ARE $16.0 \times 10.9 \pm .025$.
4. PROCESS & PLATING: SMOBC.
5. SOLDERMASK BOTH SIDES USING GLOSSY GREEN LPI.
SOLDERMASK SHALL EXIST TO WITHIN 0.1 OF PANEL EDGE.
SURFACE MOUNT FEATURES EXIST ON TOP ONLY.
6. SILKSCREEN WHITE NON-CONDUCTIVE INK COMPONENT SIDE.
SILKSCREEN MUST BE LEGIBLE, esp. LOGO, TITLES, & P/N.
7. N/C DRILL DATA PROVIDED IN ELECTRONIC FORMAT, PANELIZED.
N/C DRILL DATA INCLUDES TOOLING AND SCORING HOLES.
8. DO NOT ALTER ARTWORK, e.g. TO ADD LOGO OR DATE CODE,
EXCEPT IF AND WHERE INDICATED IN THE PANEL DRAWING.
9. ARTWORK AVAILABLE IN ELECTRONIC FORMAT, PANELIZED.
FILM PROVIDED UPON REQUEST ONLY, PANELIZED.
10. X-OUTS NEGOTIABLE. SPECIFY YOUR REQUIREMENTS IN QUOTATION.
11. V-SCORE BOTH SIDES LEAVING A WEB THICKNESS OF $.017 \pm .002$.
SCORE LINE LOCATIONS INDICATED BY SCORING HOLE CENTERS.
EXTEND ALL SCORE LINES TO EDGE OF PANEL.

DRILL TABLE
SIZE .093 OPTIONAL

SIZE	QTY 1x	QTY 30x	SYM	PLTD
.015	24	720	+	YES
.030	21	630	X	YES
.040	5	150	□	YES
.064	9	270	◇	YES
.094	4	120	⊗	YES
.093	0	26	⊕	NO
.125	0	3	⊗	NO