


NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISH ON OUTER LAYERS.
1 OZ. COPPER FINISH ON INNER LAYERS.
THICKNESS .062 +/--.006 TOTAL OF 4 LAYERS.
FLAMMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: DIMENSIONS SHOWN AND TOLERANCES TOL: +/--.0005
0.000 ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
HOLES WITH COPPER, .001 INCH THICK MIN. ALL
HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/--.003
INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
IMMERSION GOLD PLATING
6. SILKSCREEN: USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK TO ADD LOGO OR DATE CODE
BUT YOU MAY MODIFY PAD SIZE TO MEET END FINISH.
8. SCORING:



SIZE	QTY	SYM	PLTD	TOL
0.07	2	X	NO	+/--.0003
0.095	5	□	YES	+/--.0003
0.01	142	◇	YES	+/--.0003
0.035	33	⊠	YES	+/--.0003
0.187	4	+	YES	+/--.0003
0.055	10	⊕	YES	+/--.0003

Fabrication Drawing

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ± 1
2 PLACE ±.01 3 PLACE ±.005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

APPROVALS

DRAWN	INIT	DATE
CHECK		
DESIGN	Helen	4/18/07
ENGR	GUY H.	4/18/07



TITLE: LTC1605ACG/LTC1606ACG
16-Bit, 250Ksps, Single Supply ADC

SIZE	A	DEMO	DC1255A-A/B	REV.	A

SHEET 1 of 1