


REVISIONS			
REV	DESCRIPTION	APPR	DATE
A	PROTOTYPE RELEASE		


SIZE	QTY	SYM	PLTD
0.015	19	+	PLTD
0.064	6	×	PLTD



SHOWN FROM COMPONENT SIDE

### NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD THICKNESS .031 +/- .006 TOTAL OF 2 LAYERS.
2. FINISH : ALL PLATED HOLES .001 MIN./ .0015 MAX. COPPER PLATE ELECTRODEPOSITED TIN-LEAD COMPOSITION BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC).
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT.
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
5. UNUSED SMD COMPONENTS SHOULD BE FREE OF SOLDER.
6. FABRICATE EACH PANEL BY "TAB ROUTE AND RETAIN" WITH "RAT-BITES" ON THE TABS.
7. PLEASE LOOK AT THE READ ME FILE FOR THE OTHER REQUIREMENTS.

<b>APPROVALS</b>			 <b>LINEAR TECHNOLOGY</b> 1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE		
CHECK			<b>TITLE: FABRICATION DRAWING</b> <b>1 WATT CCFL CONTROLLER</b>	
DESIGN	KIM T.	06-26-02		
ENGR	DAVID C.	06-26-02		
SIZE A DEMO DC510A-1 * LTC1697EMS REV. A				
SCALE = NONE			DES- 0000 SHT 1 of 1	