

RELIABILITY REPORT



RELIABILITY DATA
LTC1745 / LTC1746 / LTC1747 / LTC1748 / LTC1749 / LTC1750

8/21/2006

• OPERATING LIFE TEST

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE HOURS ⁽¹⁾ AT +125°C	NUMBER OF ⁽²⁾ FAILURES
SSOP/TSSOP	384 384	0318	0421	384.00 384.00	0 0

• PRESSURE COOKER TEST AT 15 PSIG, +121°C

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE HOURS	NUMBER OF FAILURES
SSOP/TSSOP	1,401 1,401	0209	0547	384.76 384.76	0 0

• TEMP CYCLE FROM -65°C to +150°C

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE CYCLES	NUMBER OF FAILURES
SSOP/TSSOP	1,221 1,221	0209	0547	1,070.93 1,070.93	0 0

• THERMAL SHOCK FROM -65°C to +150°C

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE CYCLES	NUMBER OF FAILURES
SSOP/TSSOP	783 783	0209	0547	633.50 633.50	0 0

(1) Assumes Activation Energy = 0.7 Electron Volts

(2) Failure Rate Equivalent to +55°C, 60% Confidence Level = 30.82 FITS

(3) Mean Time Between Failures in Years = 3,701

Note: 1 FIT = 1 Failure in One Billion Hours.