



REVISIONS			
REV	DESCRIPTION	APPR	DATE

NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.  
2 OZ. COPPER FINISHED.  
THICKNESS .062 +/- .006 TOTAL OF 2 LAYERS.  
FLAMABILITY RATING: 94 V-0 MINIMUM .
3. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.  
HOLE LOCATION TOLERANCES ARE +/- .003 INCH IN RELATION TO CENTER
4. SIZE: DIMENSIONS AND TOLERANCES SHOWN.  
0.000 ARE PRIMARY DATUMS.
5. SOLDER MASK : SMOBC USING LPI BOTH SIDES COLOR GREEN.
6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
8. SCORING:




FAB DRAWING



SIZE	QTY	SYM	PLTD
65	14	+	PLTD
35	20	X	PLTD
10	84	□	PLTD
70	2	◇	NPLTD

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES ON ANGLE ±1  
2 PLACE ±.01 3 PLACE ±.005  
INTERPRET DIM AND TOL  
PER ASME Y14.5M - 1994

APPROVALS			 LINEAR TECHNOLOGY		1630 McCarthy Blvd. Milpitas, CA 95035 Ph: (408)432-1900	
					TITLE: LTC1859CC, 8-Channel, 16-Bit, 100ksps SoftSpan ADC	
DRAWN	INIT	DATE				
CHECK						
DESIGN	JUNE WU	6/15/03				
ENGR	M. Thoren	8/2/00				
			SIZE	A	DC682A	REV. A
SCALE = NONE			DES-250050		SHT 1 of 1	