



NOTES : Unless Otherwise Specified

- 1. FAB PER IPC-A-600.
- 2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
 - 2 OZ. COPPER FINISH ON OUTER LAYERS.
 - 1 OZ. COPPER FINISH ON INNER LAYERS.
- 3. SIZE: DIMENSIONS AND TOLERANCES SHOWN.
 - THICKNESS .062 +/- .006 TOTAL OF 6 LAYERS.
 - FLAMABILITY RATING: 94 V-0 MINIMUM.
 - 0.00 ARE PRIMARY DATUMS.
- 4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
 - HOLE SIZES ARE SPECIFIED AFTER PLATING.
 - HOLE LOCATION TOLERANCES ARE +/- .003
 - INCH IN RELATION TO CENTER
- 5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
 - SILVER IMMERSION OR LEAD FREE SOLDER BOTH SIDES.
- 6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
- 7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.



SIZE	QTY	SYM	PLTD
10	502	+	PLTD
65	8	X	PLTD
35	15	□	PLTD
187	4	◇	NPLTD
70	2	⊗	NPLTD
15	5	⊗	PLTD



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ±1
2 PLACE ±.01 3 PLACE ±.005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

APPROVALS

DRAWN	INIT	DATE
CHECK		
DESIGN	J. Wu	2/14/06
ENGR	C. Pei	2/14/06

1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: 16-BIT ADC DRIVERS

SIZE A DEMO DC1058A REV. A

SCALE = NONE

SHT 1 of 1