


REVISION HISTORY				
ECO	REV	DESCRIPTION	APP. ENG.	DATE
-	2	PRODUCTION	GUY H.	09-21-15

NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. INSTALL SHUNTS AS SHOWN.
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
7. INSTALL STANDOFFS AS SHOWN BELOW:



8. MARK EACH ASSEMBLY TYPE, SUFFIX, NUMBER OF -BIT, KSPS RATE, AND -CHANNEL IN THE WHITE BLOCK AREAS WITH BLACK PERMANENT MARKER AS SHOWN IN TABLE BELOW:

ASSY TYPE	U1	SUFFIX	-BIT	Ksps	-CHANNEL
-A	LTC2335-18	35-18	18	1000	8
-B	LTC2335-16	35-16	16	1000	8

APPROVALS

PCB DES.	KIM T.
APP ENG.	GUY H.



1630 MCCARTHY BLVD
MILPITAS, CA 95035
PH: (408)432-1900
www.linear.com
LTC CONFIDENTIAL-
FOR CUSTOMER USE ONLY


TITLE: TOP ASSEMBLY DRAWING
8-CHANNEL, SOFTSPAN,
HIGH SPEED, SERIAL, SAR, ADC

SIZE N/A	IC NO. LTC23XXILX FAMILY DEMO CIRCUIT 2412A	REV. 2
-------------	---	-----------

SCALE = NONE

FILENAME: DC2412A-2.PCB

SHT 1 OF 2



8