



REVISION HISTORY				
ECO	REV	DESCRIPTION	APPROVED	DATE
-	3	PRODUCTION	GUY H.	04-19-10




NOTES: UNLESS OTHERWISE SPECIFIED

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4
FINISHED THICKNESS TO BE 0.062" +/-0.005"
4-LAYER BOARD, 2 OZ. CU ON OUTER LAYERS,
1 OZ. CU ON INNER LAYERS,
FLAMMABILITY RATING: 94 V-2 MINIMUM.
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00" ARE PRIMARY DATUMS.
4. FINISH: SMOBC USING LPI BOTH SIDES, COLOR GREEN.
GOLD IMMERSION. LEAD FREE SOLDER CAN BE USED
FOR PROTOTYPE BOARDS.
SILKSCREEN: WHITE NON-CONDUCTIVE EPOXY INK.
5. DRILL: PLATE THRU ALL HOLES WITH COPPER, 0.001" THICK MIN.
ALL HOLES SHALL BE DRILLED +/-0.003" WITH
RESPECT TO CTR. OF DRILLED PAD.
ALL HOLES FINISHED SIZE AFTER PLATING.
6. DROP ALL UNUSED PADS ON INNER LAYERS.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
8. PCBs ARE TO BE ROHS COMPLIANT.
9. SCORING FOR PANELIZED PCB:



DRILL TABLE				
SYM	SIZE	TOL.	QTY	PLATED
□	0.188 in	+/-0.003 in	4	YES
⊙	0.094 in	+/-0.003 in	2	YES
⊗	0.070 in	+/-0.003 in	2	NO
⊕	0.064 in	+/-0.003 in	3	YES
⊖	0.055 in	+/-0.003 in	10	YES
⊗	0.040 in	+/-0.003 in	23	YES
⊗	0.035 in	+/-0.003 in	46	YES
⊗	0.012 in	+/-0.003 in	176	YES

APPROVALS		 <div>1630 MCCARTHY BLVD MILPITAS, CA 95035 TEL: (408) 432-1900 FAX: (408) 434-0507 www.linear.com LTC CONFIDENTIAL-FOR CUSTOMER USE ONLY</div>		
PCB DES.	KT			
APP ENG.	GUY H.	TITLE: FAB DWG		
		LOW POWER, LOW NOISE ADC		
		SIZE N/A	IC NO. LTC23XXCMS FAMILY DEMO CIRCUIT 1571A	REV. 3
4/19/2010 11:35:31a		SCALE: NONE		FILENAME: DC1571A-3
				SHEET 1 OF 1