


SIZE	QTY	SYM	PLATED	TOL
10	132	+	YES	+/-0.0
187	4	X	NO	+/-0.0
65	27	□	YES	+/-0.0
70	2	◇	NO	+/-0.0
40	51	⊗	YES	+/-0.0
35	14	⊗	YES	+/-0.0
20	6	⊕	YES	+/-0.0

- ART01 = LAYER 1 (COMPONENT SIDE)
- ART02 = LAYER 2 (GND)
- ART03 = LAYER 3 (GND)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES: Unless Otherwise Specified:

- PCBS Are To Be RoHS Compliant
- Fab Per IPC-A-600
- Material: Epoxy Fiberglass, NEMA Grade FR-4, 4 Layers  
.062 +/- .005 Inch Thickness With  
2 OZ. Copper Finished On All Outer Layers,  
1 OZ. Copper On All Internal Layers.  
Flammability Rating: 94 V-2 Minimum.
- Size: Cut To Dimensions And Tolerances Shown.
- Finish: SM08C Using Wet Mask, Or LPI Both Sides, Color Green.  
Silkscreen Both Sides With White Non-conductive Ink.  
Gold Immersion Both Sides (Not Required For Prototype Boards)
- Drilling: Drill Holes Per Schedule. Plate Through  
Holes With Copper, .001 Inch Thick Min. All  
Hole Sizes Are Specified After Plating.  
Hole Location Tolerances Are +/- .003" In Relation To Center.
- Do Not Alter Artwork To Add Logo Or Date Code,  
May Modify Pad Size To Meet End Finish.
- Scoring: (Not Required For Prototype Boards)



Fabrication Drawing

APPROVALS		LINEAR TECHNOLOGY		1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE			
CHECK	KL				
DESIGN					
ENGR					
Title: LTC2754AIUKG-16			16-Bit Quad Serial Precision SoftSpan Iout DAC		
Size: Demo Circuit 1546A			Rev. A		
Scale = None			Design #		
			Sht: 1 of 1		