



NOTES : Unless Otherwise Specified

- 1. FAB PER IPC-A-600.
- 2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISHED ON OUTER LAYERS.
THICKNESS .062 +/- .006 TOTAL OF 2 LAYERS.
FLAMABILITY RATING: 94 V-0 MINIMUM .
- 3. SIZE: DIMENSIONS AND TOLERANCES SHOWN.
0.000 ARE PRIMARY DATUMS.
- 4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
HOLES WITH COPPER, .001 INCH THICK MIN. ALL
HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/- .003
INCH IN RELATION TO CENTER
- 5. SOLDER MASK : SMOBC USING LPI BOTH SIDES COLOR GREEN.
- 6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
- 7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.



SIZE	QTY	SYM	PLTD
35	27	+	PLTD
65	12	X	PLTD
95	20	□	PLTD
187	4	◇	PLTD
15	152	⊗	PLTD
70	2	⊗	NPLTD

FAB DRAWING

APPROVALS				LINEAR TECHNOLOGY		1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE					
CHECK							
DESIGN	JUNE WU	12/11/03	TITLE:				
ENGR	T. Digiacomo	12/11/03	LTC2922 Series, Tracker/Sequencer Demo Board				
			SIZE	A	DEMO	DC740A	REV. A
SCALE = NONE			DES-250059			SHT 1 of 1	

