

LTC2972 Programming Board for 2-Channel PMBus Power System Manager

DESCRIPTION

The DC2691A programming board contains the circuitry needed to program and verify the EEPROM of the [LTC®2972](#). It is shipped with a clamshell style programming socket installed. The LTpowerPlay® *.proj file that corresponds to the factory default configuration can be found in the GUI.

To properly program and verify the contents of the EEPROM, download and install the LTpowerPlay software (GUI).

<http://www.linear.com/ltpowerplay/>

You also need a Linear Technology DC1613 USB to I²C/SMBus/PMBus Controller.

Demo System Required Hardware

- Windows PC
- USB-to-I²C/SMBus/PMBus Controller (DC1613)
- DC2691A

Demo System Required Software

- LTpowerPlay

Power System Manager Features

- Sequence, Trim, Margin, Supervise Power Supplies
- Manage Faults, Monitor Telemetry, Create Fault Logs
- PMBus Compliant Command Set
- Supported by LTpowerPlay GUI
- Margin or Trim Supplies to ±0.25% Accuracy
- Monitor Input Current (±1%) and Accumulate Energy
- Fast OV/UV Supervisors per Channel
- Supports Multi-Channel Fault Management
- Automatic Fault Logging to Internal EEPROM
- Operates Autonomously without Additional Software
- OV/UV V_{OUT} and One V_{IN} Supervisor
- Monitor V_{IN}, V_{OUT}, I_{IN}, I_{OUT} and Temperature
- Time-Based Output Sequencer
- I²C/SMBus Serial Interface
- Can Be Powered from 3.3V, or 4.5V to 15V
- Connect Directly to Regulator IMON Pins
- Available in a 44-Pin 6mm × 7mm QFN Package

Design files for this circuit board are available at
<http://www.linear.com/demo/DC2691A>

LT, LT, LTC, LTM, Linear Technology, the Linear logo and LTpowerPlay are registered trademarks of Analog Devices, Inc. All other trademarks are the property of their respective owners.




Figure 1. LTC2972 Programming Setup Using DC2691A

DC2691A DETAILS

What You Can Do with the DC2691A

1. Compare the contents of the LTC2972's EEPROM against any LTpowerPlay Project File. (Verify)
2. Program the contents of the LTC2972's EEPROM using any LTpowerPlay Project File. (Program and Verify)




Figure 2. DC2691A Top Side Details

LTPOWERPLAY GUI SOFTWARE

LTpowerPlay is a powerful Windows-based development environment that supports Linear Technology Power System Management ICs with EEPROM. The software supports a variety of different tasks. You can use LTpowerPlay to evaluate Linear Technology ICs by connecting to a demo board system. LTpowerPlay can also be used in an offline mode (with no hardware present) in order to build a multichip configuration file that can be saved and re-loaded at a later time. LTpowerPlay provides unprecedented diagnostic and debug features. It becomes a valuable diagnostic tool during board bring-up to program or tweak the power management scheme in a system or to diagnose power issues when bringing up

rails. LTpowerPlay utilizes the DC1613 I²C/SMBus/PMBus Controller to communicate with one of many potential targets, including the DC2691A programming board or a customer board. The software also provides an automatic update feature to keep the software current with the latest set of device drivers and documentation. The LTpowerPlay software can be downloaded from:

<http://www.linear.com/ltpowerplay>

To access technical support documents for LTC Power System Management products visit “Help, View Online Help” on the LTpowerPlay menu.




Figure 3. Screenshot of the LTpowerPlay GUI

DEMO MANUAL DC2691A

QUICK START PROCEDURE

The DC2691A programming board makes it easy to program and verify the EEPROM contents of the device.

1. Place jumpers and switches in the following default positions.

WP: OFF

ASEL1: L


ASEL0: L

S1: OFF

NOTE: By default, ASEL0 and ASEL1 jumpers are both set to low (L). If you wish to program a device with an address other than 0x5C, adjust ASEL0 and ASEL1 jumpers appropriately. Consult device data sheet for details.

2. Connect USB controller to your PC. Plug the ribbon cable into connector J1 of the DC2691A programming board.

3. Open the socket lid. Place the IC inside with pin 1 located in the upper left corner. See Figure 4.



Pin 1 indicators

Figure 4. Open Clamshell Lid

QUICK START PROCEDURE

4. Close lid. It will snap into place. See Figure 5.

NOTE: Removal and insertion of the IC should be done with either tweezers or a vacuum suction device, and with the power switch S1 set to OFF.




Figure 5. DC1613 Ribbon Cable Attached and Lid Closed

5. Set the power switch S1 to the ON position. The VDD33 LED will illuminate, indicating the on-chip regulator is providing internal power.
6. Launch the LTpowerPlay software from your PC. The LT Device Programmer window will appear. Click "..." next to the selection box and select your .proj file to program the device.




Figure 6. LT Device Programmer

QUICK START PROCEDURE

7. Click the Program and Verify button, and wait for the process to complete.

a. LTpowerPlay is ready to program/verify the device.
8. Prior to removing the device from the socket, set the power switch, S1, to the off position to remove power from the device. The USB ribbon cable may remain connected to programing board.
9. To program another device, repeat Steps 3 through 5, then Steps 7 and 8. LTpowerPlay’s Programming Utility does not need to be closed.




Figure 7. Ready To Program

- b. After the process is complete, you will see “Successfully Programmed and Verified Device” in the status bar at the bottom.





Figure 8. Successfully Programmed

SCHEMATIC DIAGRAM



DEMO MANUAL DC2691A

DEMONSTRATION BOARD IMPORTANT NOTICE

Linear Technology Corporation (LTC) provides the enclosed product(s) under the following **AS IS** conditions:

This demonstration board (DEMO BOARD) kit being sold or provided by Linear Technology is intended for use for **ENGINEERING DEVELOPMENT OR EVALUATION PURPOSES ONLY** and is not provided by LTC for commercial use. As such, the DEMO BOARD herein may not be complete in terms of required design-, marketing-, and/or manufacturing-related protective considerations, including but not limited to product safety measures typically found in finished commercial goods. As a prototype, this product does not fall within the scope of the European Union directive on electromagnetic compatibility and therefore may or may not meet the technical requirements of the directive, or other regulations.

If this evaluation kit does not meet the specifications recited in the DEMO BOARD manual the kit may be returned within 30 days from the date of delivery for a full refund. THE FOREGOING WARRANTY IS THE EXCLUSIVE WARRANTY MADE BY THE SELLER TO BUYER AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. EXCEPT TO THE EXTENT OF THIS INDEMNITY, NEITHER PARTY SHALL BE LIABLE TO THE OTHER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

The user assumes all responsibility and liability for proper and safe handling of the goods. Further, the user releases LTC from all claims arising from the handling or use of the goods. Due to the open construction of the product, it is the user's responsibility to take any and all appropriate precautions with regard to electrostatic discharge. Also be aware that the products herein may not be regulatory compliant or agency certified (FCC, UL, CE, etc.).

No License is granted under any patent right or other intellectual property whatsoever. **LTC assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or any other intellectual property rights of any kind.**

LTC currently services a variety of customers for products around the world, and therefore this transaction **is not exclusive**.

Please read the DEMO BOARD manual prior to handling the product. Persons handling this product must have electronics training and observe good laboratory practice standards. **Common sense is encouraged.**

This notice contains important safety information about temperatures and voltages. For further safety concerns, please contact a LTC application engineer.

Mailing Address:

Linear Technology
1630 McCarthy Blvd.
Milpitas, CA 95035

Copyright © 2004, Linear Technology Corporation