


REVISION HISTORY				
ECO	REV	DESCRIPTION	APPROVED	DATE
-	4	4TH PROTOTYPE	KALIN L.	08-26-2011

SIZE	QTY	SYM	PLATED	TOL
190	4	+	YES	+/-0.003
15	283	X	YES	+/-0.003
35	56	□	YES	+/-0.003
70	2	◇	NO	+/-0.003
40.35	50	X	YES	+/-0.003
67	15	X	YES	+/-0.003
30	23	⊖ ^A	YES	+/-0.003
37	22	⊖ ^B	YES	+/-0.003
22	4	⊖ ^C	YES	+/-0.003
12	7	⊖ ^D	YES	+/-0.003

NOTES: UNLESS OTHERWISE SPECIFIED

- FAB PER IPC-A-600.
- MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.
-FINISHED THICKNESS TO BE 0.062" +/- .005"
-TOTAL OF 4 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.
-FLAMMABILITY RATING: 94 V-0 MINIMUM.
- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00" ARE PRIMARY DATUMS.
- DRILLING: -DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001" THICK MIN.
-ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
-HOLE LOCATION TOLERANCES ARE +/-0.003" IN RELATION TO CENTER
- FINISH: -ENIG USING LPI BOTH SIDES, COLOR GREEN.
-FOR SILKSCREENS: USE WHITE NON-CONDUCTIVE INK.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE. PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
- PCBS ARE TO BE RoHS COMPLIANT.
- SCORING FOR PANELIZED PCB (PRODUCTION FAB ONLY):



APPROVALS			<small>1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 www.linear.com LTC CONFIDENTIAL - FOR CUSTOMER USE ONLY</small>	
PCB DES.	S. M.		TITLE: FAB DRAWING QUAD DIGITAL POWER SUPPLY MANAGER WITH EEPROM	SIZE
APP ENG.	KALIN L.	IC NO. LTC2974CUP DEMO CIRCUIT 1809A	B	4
SCALE = NONE		FILENAME: 1809A-4.PCB	SHT 1 OF 1	