



SIZE	QTY	SYM	PLTD	TOL
0.07	2	+	NO	+/-0.003"
0.035	9	X	YES	+/-0.003"
0.094	4	□	YES	+/-0.003"
0.012	15	◇	YES	+/-0.003"

1. FAB PER IPC-A-600
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4  
FINISHED THICKNESS TO BE 0.062" +/- .005"  
TOTAL OF 4 LAYERS WITH 2 OZ. CU ON THE  
OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.  
FLAMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.  
0.00" ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH  
HOLES WITH COPPER, 0.001" THICK MIN.  
ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.  
HOLE LOCATION TOLERANCES ARE +/-0.003"  
IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES, COLOR GREEN.  
WHITE TIN IMMERSION (OMIKRON).  
FOR SILKSCREEN: USE WHITE NON-CONDUCTIVE INK.
6. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
7. SCORING FOR PANELIZED PCB:



APPROVALS			 <b>LINEAR TECHNOLOGY</b> 1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 LTC CONFIDENTIAL FOR CUSTOMER USE ONLY
	INIT	DATE	
DRAWN			
CHECK			
DESIGN	KIM T.	03-27-06	
ENGR	JULIAN Z.	03-27-06	TITLE: FABRICATION DRAWING 500mA LOW NOISE, HIGH EFFICIENCY CHARGE PUMP
			SIZE A DEMO DC863A-LTC3203 REV. A
SCALE = NONE			SHT 1 of 1