DC1128a.pcb - Fri May 18 15:22:47 2007

REVISIONS			
REV	DESCRIPTION	APPR	DATE



NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
   2 OZ. COPPER FINISH ON OUTER LAYERS.
   1 OZ. COPPER FINISH ON INNER LAYERS.
   THICKNESS .062 +/-.006 TOTAL OF 4 LAYERS.
   FLAMABILITY RATING: 94 V-O MINIMUM .
3. SIZE: DIMENSIONS SHOWN AND TOLERANCES TOL: +/-0.010
   0.000 ARE PRIMARY DATUMS.
4. DRILLLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
   HOLES WITH COPPER, .001 INCH THICK MIN. ALL
   HOLE SIZES ARE SPECIFIED AFTER PLATING.
   HOLE LOCATION TOLERANCES ARE +/-.003
   INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
   IMMERSION SILVER SOLDER PLATING
6. SILKSCREEN : BOTH SIDES USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
8. SCORING:



Fabrication Drawing

SIZE	QTY	SYM	PLTD	TOL
0.07	2	X	NO	+/-0.003
0.095	6	□	YES	+/-0.003
0.01	17	◇	YES	+/-0.003
0.035	19	⋈	YES	+/-0.003

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ± 1
2 PLACE ± .01 3 PLACE ± .005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

APPROVALS		
	INIT	DATE
DRAWN		
CHECK		
DESIGN	Helen	12/14/06
ENGR	George Yu	12/14/06
SCALE = NONE		

LINEAR TECHNOLOGY
1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: LTC3419EDD, 2.25MHz Dual-Output 600mA Monolithic Step-Down DC/DC Supply

SIZE	DEMO	REV.
A	DC1128A	A

DES-250 | SHEET 1 of 1