



REVISIONS			
REV	DESCRIPTION	APPR	DATE



SIZE	QTY	SYM	PLATED	TOL
95	5	+	YES	+/-0.0
35	13	X	YES	+/-0.0
70	2	□	NO	+/-0.0
10	8	◇	YES	+/-0.0

- NOTES: UNLESS OTHERWISE SPECIFIED**
1. FAB PER IPC-A-600. PCBs ARE TO BE ROHS COMPLIANT.
 2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISH ON OUTER LAYERS.
1 OZ. COPPER FINISH ON INNER LAYERS.
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS.
FLAMMABILITY RATING: 94 V-0 MINIMUM .
 3. SIZE: DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
 4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/- .003 INCH IN RELATION TO CENTER
 5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
GOLD IMMERSION BOTH SIDES.
 6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
 7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE
BUT YOU MAY MODIFY PAD SIZE TO MEET END FINISH.
 8. SCORING: (FOR PRODUCTION RUN ONLY)



FAB DRAWING

APPROVALS		LINEAR TECHNOLOGY	
PCB DESIGNER	DATE	1630 McCarthy Blvd.	
J. WU	4/18/07	Milpitas, CA 95035	
ENGINEER	DATE	PH: (408)432-1900	
F. Hoffert	4/18/07		
CHECK			
TITLE: LTC3539EDCB/LTC3539EDCB-2		2A Synchronous Boost Converter	
SIZE A		REV. 1	
DC1260A		SHT 1 of 1	

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ± 1
2 PLACE ± .01 3 PLACE ± .005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

SCALE = NONE