


REVISIONS		
REV	APPR	DATE

NOTES: UNLESS OTHERWISE SPECIFIED:

- ARTWORK P/N DEMO CIRCUIT 1334A
- FAB PER IPC-A-600. 4-Layers.
- MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4
.062 +/- .005 INCH THICKNESS WITH 2 OZ.
COPPER FINISH ON TWO OUTER LAYERS AND
1 OZ. COPPER ON TWO INTERNAL LAYERS.
FLAMMABILITY RATING: 94 V-2 MINIMUM .
- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
- BOARD: SELECTIVE PLATED BOARD. SOLDER
MASK OVER BARE COPPER, COLOR, GREEN LPI.
GOLD IMMERSION (ENIG) BOTH SIDES.
SILKSCREEN BOTH SIDES WITH WHITE NON-
CONDUCTIVE INK.
PLATE THRU ALL HOLES WITH COPPER
MIN. PLATING THICKNESS: 1 OZ. EXCEPT
WHERE PLATING NOT REQUIRED
- DRILL: ALL HOLES SHALL BE DRILLED +/- .003 INCH
WITH RESPECT TO CTR. OF DRILLED PAD.
ALL HOLES FINISHED SIZE AFTER PLATING.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO, DATE CODE OR
ELECTRICAL TEST STAMP, BUT YOU MAY MODIFY PAD SIZE TO
MEET END FINISH.
- SCORING FOR PANELIZED PCB: "PRODUCTION RUN ONLY"



- DO NOT ALTER SOLDER MASK MAINTAIN .0018" OVERSIZE
ON SMT PADS. A .005" WEBBING IS REQUIRED BETWEEN SMD PADS.
- PCB'S ARE TO BE ROHS COMPLIANT.

Fabrication Drawing

SIZE	QTY	SYM	PLATED	TOL
0.072	2	+	YES	+/-0.0
0.087	4	X	YES	+/-0.0
0.035	33	□	YES	+/-0.0
0.03	4	◇	YES	+/-0.0
0.031	50	Σ	YES	+/-0.0
0.084	14	Δ	YES	+/-0.0
0.01	45	⊕	YES	+/-0.0
0.083	7	⊞	YES	+/-0.0
0.0311	3	⊞	YES	+/-0.0

Linear Tech. Corp.
Demo Circuit 1334A

Fabrication Drawing

**LINEAR**
TECHNOLOGY

1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: LTC3576EUF
Switching Power Manager + USB On-The-Go
OVP + HV Buck VC Control + 3 Bucks

SIZE	NONE	REV.	A
------	------	------	---

DES-23xxxx	SHT 1 of 1
------------	------------

SCALE = NONE