



REV	APPR	DATE
-----	------	------


NOTES: UNLESS OTHERWISE SPECIFIED:

1. ARTWORK P/N Demo Circuit 1402A-A/B
 2. FAB PER IPC-A-600. 4-Layers.
 3. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4
 .062 +/- .005 INCH THICKNESS WITH 2 OZ.
 COPPER FINISH ON TWO OUTER LAYERS AND
 1 OZ. COPPER ON TWO INTERNAL LAYERS.
 FLAMMABILITY RATING: 94 V-2 MINIMUM .
 4. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
 5. BOARD: SELECTIVE PLATED BOARD. SOLDER
 MASK OVER BARE COPPER, COLOR, GREEN LPI.
 GOLD IMMERSION (ENIG) BOTH SIDES.
 SILKSCREEN : USING WHITE NON-CONDUCTIVE INK.
 PLATE THRU ALL HOLES WITH COPPER
 MIN. PLATING THICKNESS: 1 OZ. EXCEPT
 WHERE PLATING NOT REQUIRED
 6. DRILL: ALL HOLES SHALL BE DRILLED +/- .003 INCH
 WITH RESPECT TO CTR. OF DRILLED PAD.
 ALL HOLES FINISHED SIZE AFTER PLATING.
 7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE OR
 ELECTRICAL TEST STAMP, BUT YOU MAY MODIFY PAD SIZE TO
 MEET END FINISH.
 8. SCORING FOR PANELIZED PCB: "PRODUCTION RUN ONLY"
- 
9. DO NOT ALTER SOLDER MASK MAINTAIN .0018" OVERSIZE
 ON SMT PADS. A .005" WEBBING IS REQUIRED BETWEEN SMD PADS.
 10. PCB'S ARE TO BE ROHS COMPLIANT.
 11. BOARDS WILL BE SERIALIZED USING BOTTOM SILKSCREEN DIGITS 8888.



Fabrication Drawing

SIZE	QTY	SYM	PLATED	TOL
0.072	2	+	NO	+/-0.003
0.071	184	X	YES	+/-0.003
0.01				
0.035	36	□	YES	+/-0.003
0.063	13	◇	YES	+/-0.003
0.19	4	⊗	YES	+/-0.003
0.094	15	⊗	YES	+/-0.003
0.035	2	⊗	NO	+/-0.003
0.031H	3	+	NO	+/-0.003
0.031	21	+	YES	+/-0.003

APPROVALS				1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900
DRAWN	INIT	DATE	TITLE:	LTC3577EUFF/LTC3577EUFF-1
CHECK	N/C	4/21/09	Highly Integrated 6-Channel Portable PMIC	
DESIGN	N/C	1/19/09	SIZE	NON
ENGR	MM		REV.	A
			DC1402A-A/B	
SCALE = NONE			DES-23axxxx SHT 1 of 1	