


SIZE	QTY	SYM	PLTD	TOL
40	3	+	YES	+/-0.0
65	7	X	YES	+/-0.0
10	46	□	YES	+/-0.0
70	2	◇	NO	+/-0.0
94	6	⊗	YES	+/-0.0
15	19	⊗	YES	+/-0.0

- ART01 = LAYER 1 (COMPONENT SIDE)
- ART02 = LAYER 2 (GND)
- ART03 = LAYER 3 (GND)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES : Unless Otherwise Specified


- MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
THICKNESS .062 +/--.006 TOTAL OF 4 LAYERS
- FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
WHITE TIN IMMERSION (OMIKRON) BOTH SIDES.
- BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC)
- SOLDER MASK : BOTH SIDES USING GREEN LPI
- SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
- ALL DIMENSIONS ARE IN INCHES
- SCORING:



Fabrication Drawing

APPROVALS

DRAWN	INIT	DATE
CHECK		
DESIGN		
ENGR		



1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: LTC3736UF-2, 2-Phase Dual Synchronous
Step-Down Converter with Output Tracking

SIZE	NONE	Demo Circuit 922A	REV.
SCALE = NONE			DESIGN #
			SHT 1 of 1