


Top Side

SIZE	QTY	SYM	PLTD	TOL
63	7	+	YES	+/-3Mil
94	6	×	YES	+/-3Mil
10	82	□	YES	+/-3Mil
70	2	◇	NO	+/-3Mil
31	19	⊗	YES	+/-3Mil

NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.  
2 OZ. COPPER FINISH ON OUTER LAYERS.  
1 OZ. COPPER FINISH ON INNER LAYERS.  
THICKNESS .062 +/--.006 TOTAL OF 4 LAYERS.  
FLAMABILITY RATING: 94 V-0 MINIMUM .  
0.000 ARE PRIMARY DATUMS .
3. SIZE: DIMENSIONS SHOWN AND TOLERANCES TOL: +/--.010
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.  
HOLE LOCATION TOLERANCES ARE +/--.003 INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.  
IMMERSION SILVER SOLDER PLATING
6. SILKSCREEN: BOTH SIDES USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
8. SCORING:



Fabrication Drawing

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES ON ANGLE ± 1  
2 PLACE ±.01 3 PLACE ±.005  
INTERPRET DIM AND TOL  
PER ASME Y14.5M - 1994

APPROVALS	
DRAWN	INIT
CHECK	DATE
DESIGN	Helen 3/08/07
ENGR	George 3/08/07
SCALE = NONE	

**LINEAR TECHNOLOGY**

1630 McCarthy Blvd.  
Milpitas, CA 95035  
PH: (408)432-1900

TITLE: LTC3826EG-1 Wide Output Range  
Dual-Output Synchronous Step Down Supplies

SIZE A DEMO DC1235A REV. A

DES-250 SHEET 1 of 1