

TOP SIDE SHOWN

REVISION HISTORY				
ECO	REV	DESCRIPTION	APPROVAL	DATE
	2	PRODUCTION	MIKE S.	04/26/11

NOTES: UNLESS OTHERWISE SPECIFIED,

1. FAB PER IPC-A-600
2. MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.
   -FINISHED THICKNESS TO BE 1.6 ±0.13
   -TOTAL OF 6 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.
   -FLAMMABILITY RATING: 94 V-O MINIMUM .
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN. 0.00 ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.025 THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING. HOLE LOCATION TOLERANCES ARE ±0.08 IN RELATION TO CENTER
5. FINISH: -SMOBC USING LPI BOTH SIDES, COLOR GREEN.
   -GOLD IMMERSION BOTH SIDES.
   -SILKSCREEN BOTH SIDES WITH WHITE NON-CONDUCTIVE INK.
6. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE. PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
7. PCBS SHALL BE RoHS COMPLIANT.
8. SCORING FOR PANELIZED PCB (PRODUCTION FAB ONLY):



LAYER STRUCTURE



SIZE	QTY	SYM	PLATED	TOL
0.25	254	⊕	YES	+/-0.08
0.76	14	⊡	YES	+/-0.08
1.78	2	◈	NO	+/-0.13
2.41	14	⧖	YES	+/-0.13
5.21	6	⋈	YES	+/-0.25

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS
TOLERANCES ON ANGLE ±1°
.XX ± 0.254
.XXX ± 0.127
INTERPRET DIM AND TOL PER ASME Y14.5M-1994
THIRD ANGLE PROJECTION

DO NOT SCALE DRAWING

APPROVALS	
PCB DES.	MI
APP. ENG.	MIKE S.

SCALE: NONE

LINEAR TECHNOLOGY
1630 MCCARTHY BLVD
MILPITAS, CA 95035
PH: (408)432-1900
www.linear.com
LTC CONFIDENTIAL-
FOR CUSTOMER USE ONLY

TITLE: FABRICATION DRAWING,
DUAL OUTPUT SYNCHRONOUS BUCK CONVERTER

SIZE	IC NO.	REV
N/A	LTC3855EFE DEMO CIRCUIT 1617A	2

FILENAME: 1617A-2.PCB

SHT 1 of 1