



For ADI Customer Use Only




REVISION HISTORY

ECO	REV	DESCRIPTION	DATE	APPROVED
	1	PROD	06/13/19	<i>gpo</i>

NOTES: UNLESS OTHERWISE SPECIFIED,

- ARTWORK P/N DC2118B REV 1.
- FAB PER IPC-A-600
- PCB SHALL MEET RoHS COMPLIANCE.
- MATERIAL:
 - LAMINATE: EPOXY FIBERGLASS, NEMA GRADE FR-4
FLAMMABILITY RATING: 94 V-2 MINIMUM.
 - THICKNESS: 1.6 +/- 0.1 mm
 - CLAD: 2 OZ. (50um) EXTERNAL LAYERS.
1 OZ. (25um) COPPER ON TWO INTERNAL LAYERS.
- FINISH:
 - COATING: SOLDERMASK OVER BARE COPPER,
COLOR, GREEN LPI.
 - PLATING: GOLD IMMERSION BOTH SIDES.
 - SILKSCREEN: BOTH SIDES WITH WHITE
NON-CONDUCTIVE INK.
- TOLERANCES:
 - WARPAGE: (0,0075mm) MAX. ALONG THE LONGEST
DIAG. AS PER IPC-TM650 METHOD 2.4.22.
 - ETCHING: +0.03mm, -0.3mm OF MASTER PATTERN.
 - REGISTRATION: 0.075mm MAX.
 - MASK THICKNESS: 0.025mm MIN., 0.075mm MAX.
 - HOLE PLATING: 22um +/- 3um.
- SIZE:
 - CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
- HOLE DIAMETERS ARE POST-PLATED SIZES.
- DEBURR AND BREAK ALL SHARP EDGES.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR
DATE CODE.
- SCORING:


SIZE	QTY	SYM	PLATED	TOL
0.25	118	+	YES	+/-0.08
0.9	21	X	YES	+/-0.08
1.8	2	□	NO	+/-0.13
2.41	18	◇	YES	+/-0.13
4.75	4	⊗	NO	+/-0.13



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MILLIMETERS
TOLERANCES ON ANGLE ± 1°

.XX ± 0.25
.XXX ± 0.127

THIRD ANGLE PROJECTION



DO NOT SCALE DRAWING

CONTRACT NO.

APPROVALS

DATE

DRAWN

06/13/19

CHECKED

APPROVED

06/13/19

DESIGNED BY

ANALOG
DEVICESPOWER BY
LINEAR™

www.analog.com
www.linear.com

1630 McCarthy Blvd.
Milpitas, CA 95035
Phone: (408) 432-1900

TITLE

FAB, LTC4040EUF/D/LTC4041EUF/D,
BATTERY CHARGER BACKUP

SIZE
A

CAGE CODE

DWG NO.

DC2118B

REV
1

SCALE 1/1

FILENAME: 2118a-5.PCB

SHEET 1 OF 1