


Linear Tech. Corp.
Demo Circuit 672 RevA


Component Side



REVISIONS			
REV		APPR	DATE


NOTES: Unless Otherwise Specified

1. MATERIAL: 4 LAYERS, 0.062" THK. FR-4 GLASS EPOXY 2 OZ. COPPER CLAD.
2. ALL HOLE SHALL BE PLATED THRU.
3. PLATE THRU HOLES WITH COPPER .0014 MIN. THICKNESS. ALL HOLE SIZES IN HOLE TABLE ARE AFTER PLATING.
4. SILKSCREEN: WITH WHITE EPOXY NON-CONDUCTIVE INK.
5. NO SILKSCREEN ALLOWED ON PADS LANDS.
6. SOLDER MASK: LPI, GREEN.
7. NO BLOCK SOLDERMASKING OF PADS ROWS.
8. DO NOT MAKE CHANGES ON SILKSCREEN, SUCH AS COMPANY LOGO, QC STAMPS.
9. DO NOT PLATE TOOLING(3PLCS) AND SCORING(26PLCS) HOLES.
10. SCORING:



SIZE	QTY	SYM	PLTD
125	4	+	PLTD
94	8	X	PLTD
10	13	□	PLTD
31	3	◇	PLTD
70	2	⊗	NPLTD

Fabrication Drawing

APPROVALS			 <div>1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900</div>	
	INIT	DATE		
DRAWN			TITLE: LTC4058EDD-4.2 Li-Ion Battery Charger	
CHECK				
DESIGN	RmB			
ENGR	JShannon			
			SIZE NONE	Demo Circuit 672 REV. A
SCALE = NONE			DES-230622	SHT 1 of 1