


- ART01 = LAYER 1 (COMPONENT SIDE)
- ART02 = LAYER 2 (GND)
- ART03 = LAYER 3 (SIGNAL)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
ELECTRODEPOSITED TIN-LEAD COMPOSITION
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SNOBC)
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
5. ALL DIMENSIONS ARE IN INCHES
6. SCORING:



Fabrication Drawing

SIZE	QTY	SYM	PLTD	TOL
95	11	+	YES	+/-0.0
40	16	X	YES	+/-0.0
70	2	□	NO	+/-0.0
15	16	◇	YES	+/-0.0

APPROVALS		LINEAR TECHNOLOGY		1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE			
CHECK					
DESIGN					
ENGR					
TITLE:			LTC4063EDD		
			Lithium-Ion Linear Battery Charger with LDO Regulator		
SIZE	A	DEMO BRD	735A	REV.	
SCALE = NONE			DES-		SHT 1 of 1