



SIZE	QTY	SYM	PLATED	TOL
95	8	X	YES	+/-0.0
55	8	□	YES	+/-0.0
15	41	◇	YES	+/-0.0
65	8	⊗	YES	+/-0.0
40	12	⊗	YES	+/-0.0
70	2	⊕	NO	+/-0.0

NOTES: Unless Otherwise Specified:

1. PCBs Are To Be RoHS Compliant
2. Fab Per IPC-A-600
3. Material: Epoxy Fiberglass, NEMA Grade FR-4, 2 Layers
.062 +/- .005 Inch Thickness With
2 OZ. Copper Finished On All Outer Layers,
Flammability Rating: 94 V-2 Minimum.
4. Size: Cut To Dimensions And Tolerances Shown.
0.00 Are Primary Datums.
5. Finish: SMOBC Using Wet Mask, Or LPI Both Sides, Color Green.
Silkscreen Component Side With White Non-conductive Ink.
Gold Immersion Both Sides (Not Required For Prototype Boards)
6. Drilling: Drill Holes Per Schedule. Plate Through
Holes With Copper, .001 Inch Thick Min. All
Hole Sizes Are Specified After Plating.
Hole Location Tolerances Are +/- .003" In Relation To Center.
7. Do Not Alter Artwork To Add Logo Or Date Code,
You May Modify Pad Size To Meet End Finish.
8. Scoring: (Not Required For Prototype Boards)



Fabrication Drawing

<div>APPROVALS</div>						<div>1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900</div>		
			<div>TITLE: LTC4217CFE, LTC4217CDHC-12 Positive 24V, Positive 12V Integrated Hot Swap</div>			<div>SIZE A DEMO BRD DC1051A REV.</div>		
DRAWN			INIT	DATE	<div>SCALE = NONE DES- SHT 1 of 1</div>			
CHECK			KL					
DESIGN								
ENGR								