


ART01 = LAYER 1 (COMPONENT SIDE)
ART02 = LAYER 2 (SOLDER SIDE)

NOTES: Unless Otherwise Specified:

- 1. PCBS Are To Be RoHS Compliant
- 2. Fab Per IPC-A-600
- 3. Material: Epoxy Fiberglass, NEMA Grade FR-4, 2 Layers
.062 +/- .005 Inch Thickness With
2 OZ. Copper Finished On All Outer Layers,
Flammability Rating: 94 V-2 Minimum.
- 4. Size: Cut To Dimensions And Tolerances Shown.
0.00 Are Primary Datums.
- 5. Finish: SM08C Using Wet Mask, Or LPI Both Sides, Color Green.
Silkscreen Component Side With White Non-conductive Ink.
- 6. Drilling: Drill Holes Per Schedule. Plate Through
Holes With Copper, .001 Inch Thick Min. All
Hole Sizes Are Specified After Plating.
Holes Location Tolerances Are +/- .003" In Relation To Center.
- 7. Do Not Alter Artwork To Add Logo Or Date Code,
But You May Modify Pad Size To Meet End Finish.
- 8. Scoring: (Not Required For Prototype Boards)



SIZE	QTY	SYM	PLATED	TOL
70	2	+	NO	+/-0.0
95	8	X	YES	+/-0.0
55	8	□	YES	+/-0.0
15	63	◇	YES	+/-0.0
65	8	⊗	YES	+/-0.0
40	12	⊠	YES	+/-0.0

Fabrication Drawing

APPROVALS		INIT		DATE	
DRAWN		KL			
CHECK					
DESIGN					
ENGR					
SCALE = NONE		DES-		SHT 1 of 1	

LINEAR TECHNOLOGY		1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
TITLE: LTC4218CGN, LTC4218CDHC-12			
Positive 24V, Positive 12V Hot Swap			
SIZE	DC1052A-A/B	REV.	
A			