


- ART01 = LAYER 1 ( COMPONENT SIDE )
- ART02 = LAYER 2 (GND)
- ART03 = LAYER 3 (SIGNAL)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES : Unless Otherwise Specified

- 1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD  
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS
- 2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE  
ELECTRODEPOSITED TIN-LEAD COMPOSITION  
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SNOBC)
- 3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT
- 4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
- 5. ALL DIMENSIONS ARE IN INCHES
- 6. SCORING:



SIZE	QTY	SYM	PLTD	TOL
72	2	+	NO	+/-0.0
35	14	X	YES	+/-0.0
15	99	□	YES	+/-0.0
95	5	◇	YES	+/-0.0
40	24	⊗	YES	+/-0.0
65	11	⊗	YES	+/-0.0
55	4	-A	YES	+/-0.0
60	3	-B	YES	+/-0.0

Fabrication Drawing

APPROVALS

DRAWN	INIT	DATE
CHECK		
DESIGN		
ENGR		

LINEAR TECHNOLOGY

1630 McCarthy Blvd.  
Milpitas, CA 95035  
PH: (408)432-1900

TITLE: 200W Positive 48V Hot Swap Controller With  
Current and Voltage Monitoring

SIZE A  
DC786A LTC4260CGN  
REV.

SCALE = NONE

SHT 1 of 1