REVISION HISTORY				
ECO	REV	DESCRIPTION	APP. ENG.	DATE
–	2	PRODUCTION	SAL H.	03-08-18



NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC–A–610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. INSTALL SHUNTS AS SHOWN.
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE–OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
7. INSTALL 4 STANDOFFS AS SHOWN BELOW:



APPROVALS	
PCB DES.	KIM T.
APP ENG.	SAL H.
SCALE = NONE	

ANALOG DEVICES | POWER BY LINEAR™
1630 McCARTHY BLVD.
MILPITAS, CA 95035
TEL: (408)432–1900
www.analog.com www.linear.com

TITLE: TOP ASSEMBLY DRAWING
12V/7A IDEAL DIODE CONTROLLING WITH REVERSE PROTECTION

SIZE	IC NO.	REV.
N/A	LTC4376IDHD DEMO CIRCUIT 2705A	2

FILENAME: DC2705A–2.PCB SHT 1 OF 2