



NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. NO SHUNT
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
7. INSTALL J1-J4 CONNECTORS AS SHOWN BELOW:



TOP SILKSCREEN
LINEAR TECHNOLOGY DATE: 10-23-2017
DC2524A-3 * LTC5555
PROGRAMMABLE GAIN MIXER



APPROVALS		LINEAR TECHNOLOGY	
PCB DES.	AK	1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 www.linear.com LTC CONFIDENTIAL— FOR CUSTOMER USE ONLY	
APP ENG.	WESTOM S.	TITLE: TOP ASSEMBLY DRAWING PROGRAMMABLE GAIN MIXER	
		SIZE	IC NO.
		N/A	LTC5555UFID DEMO CIRCUIT 2524A
SCALE = NONE	FILENAME: DC2524A-3	REV. 3	SHT 1 OF 2