



TOP SILKSCREEN
 ANALOG DEVICES DATE 12-11-2017
 DC2792A * LTC6820
 DUAL MASTER isoSPI ADAPTER

NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. NO SHUNTS
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
7. DO NOT INSTALL STAND OFF MH1, MH2, MH3, MH4
8. INSTALL CONNECTORS J4, J5, J6, J7 ON THE BOTTOM OF THE BOARD



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES: 0.XX" = ± 0.01 " 0.XXX" = ± 0.005 " INTERPRET DIM AND TOL PER ASME Y14.5M-1994 THIRD ANGLE PROJECTION 	APPROVALS		1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 CONFIDENTIAL- FOR CUSTOMER USE ONLY	
	PCB DES.	AK.		
	APP ENG.	JON M.	TITLE: ASSEMBLY DRAWING	
			DUAL MASTER isoSPI ADAPTER	
			SIZE N/A	IC NO. LTC6820 DC2792A 1
SCALE = NONE		FILENAME: DC2792A-1.PCB		SHT 1 OF 1