


REV	DESCRIPTION	APPR	DATE

**NOTES : Unless Otherwise Specified**

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.  
2 OZ. COPPER FINISH ON OUTER LAYERS.  
1 OZ. COPPER FINISH ON INNER LAYERS.  
THICKNESS .062 +/--.003 TOTAL OF 4 LAYERS.  
FLAMMABILITY RATING: 94 V-0 MINIMUM .  
0.000 ARE PRIMARY DATUMS.
3. SIZE: DIMENSIONS SHOWN AND TOLERANCES TOL: +/-0.010
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH  
HOLES WITH COPPER, .001 INCH THICK MIN. ALL  
HOLE SIZES ARE SPECIFIED AFTER PLATING.
5. FINISH: SWOBC USING LPI BOTH SIDES COLOR GREEN.  
HOLE LOCATION TOLERANCES ARE +/--.003  
INCH IN RELATION TO CENTER  
IMMERSION GOLD PLATING
6. SILKSCREEN: BOTH SIDES USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK TO ADD LOGO OR DATE CODE.  
BUT YOU MAY MODIFY PAD SIZE TO MEET END FINISH.
8. PCBs ARE TO BE RoHS COMPLIANT.
9. SCORING:



SIZE	QTY	SYM	PLATED	TOL
0.187	4	+	YES	+/-0.003
0.095	14	X	YES	+/-0.003
0.205	7	□	YES	+/-0.003
0.07	2	◇	NO	+/-0.003
0.035	9	⊗	YES	+/-0.003
0.01	145	⊗	YES	+/-0.003

# Fabrication Drawing

APPROVALS			
		INIT	DATE
	DRAWN		
	CHECK		
	DESIGN	Helen	4/03/08
	ENGR	Judy S.	4/03/08
			SCALE = NONE

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES ON ANGLE  $\pm 1$   
2 PLACE  $\pm .01$  3 PLACE  $\pm .005$   
INTERPRET DIM AND TOL  
PER ASME Y14.5M - 1994



1630 McCarthy Blvd.  
Milpitas, CA 95035  
PH: (408)432-1900

TITLE: LTM4615EV High Density Dual Output Step-Down Power uModule with VLDO		
SIZE	A	REV. A
DC1367A		
DES		SHEET 1 of 1

SCALE = NONE	DES	SHEET 1 of 1
--------------	-----	--------------