


SIZE	QTY	SYM	PLATED	TOL
187	4	+	NO	+/-0.0
70	2	X	NO	+/-0.0
95	12	□	YES	+/-0.0
215	6	◇	YES	+/-0.0
6	240	⊗	YES	+/-0.0
40	23	⊗	YES	+/-0.0
20	2	⊕	YES	+/-0.0

- ART01 = LAYER 1 (COMPONENT SIDE)
- ART02 = LAYER 2 (GND)
- ART03 = LAYER 3 (GND)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES: Unless Otherwise Specified:

- PCBS Are To Be RoHS Compliant
- Fab Per IPC-A-600
- Material: Epoxy Fiberglass, NEMA Grade FR-4, 4 Layers
.062 +/- .005 Inch Thickness With
2 OZ. Copper Finished On All Outer Layers,
1 OZ. Copper On All Internal Layers.
Flammability Rating: 94 V-2 Minimum.
- Size: Cut To Dimensions And Tolerances Shown.
0.00 Are Primary Datums.
- Finish: SMOBC Using Wet Mask, Or LPI Both Sides, Color Green.
Silkscreen Both Sides With White Non-conductive Ink
Gold Immersion Both Sides (Not Required For Prototype Boards)
- Drilling: Drill Holes Per Schedule. Plate Through
Holes With Copper, .001 Inch Thick Min. All
Hole Sizes Are Specified After Plating.
Hole Location Tolerances Are +/- .003" In Relation To Center.
- Do Not Alter Artwork To Add Logo Or Date Code,
May Modify Pad Size To Meet End Finish.
- Scoring: (Not Required For Prototype Boards)



Fabrication Drawing

APPROVALS

DRAWN	INIT	DATE
CHECK	KL	
DESIGN		
ENGR		

LINEAR TECHNOLOGY

1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

LTM4619EV

4.5V-28V, Dual 4A Step-Down μ Module

SIZE	DEMO BRD	DC1453A	REV.	A
A				

SCALE = NONE

SHT 1 of 1