


| REVISION HISTORY | | | |
|------------------|-----|-------------|-----------|
| ECO | REV | DESCRIPTION | APP. ENG. |
| - | 1 | PRODUCTION | YL |
| | | | 02-27-17 |


NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. INSTALL SHUNTS AS SHOWN ON ASSY DRAWING.
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
7. INSTALL 4 STANDOFFS AS SHOWN BELOW:



8 MARK ASSEMBLY TYPE AND VOUT CURRENT WITH BLACK PERMANENT MARKER BASED ON THE TABLE BELOW:

| ASSY | IC | AMP |
|------|-----------|-----|
| -A | LTM4645EY | 25 |
| -B | LTM4647EY | 30 |



APPROVALS

| | |
|--------------|----|
| PCB DES. | LT |
| APP ENG. | YL |
| | |
| | |
| SCALE = NONE | |

LINEAR

TECHNOLOGY

1630 MCCARTHY BLVD

MILPITAS, CA 95035

PH: (408)432-1900

www.linear.com

LTC CONFIDENTIAL -

FOR CUSTOMER USE ONLY

TITLE: TOP ASSEMBLY DRAWING

SINGLE-OUTPUT, HIGH EFFICIENCY STEP-DOWN μMODULE REGULATOR

| | | | |
|-----------|--------------|---------------------|------|
| SIZE | IC NO. | LTM4645EY/LTM4647EY | REV. |
| N/A | DEMO CIRCUIT | 2681A(A,B) | 1 |
| FILENAME: | | DC2681A-1.PCB | |
| | | SHT 1 OF 2 | |