


4.55




SIZE	QTY	SYM	PLATED	TOL
0.008	114	\oplus^A	YES	+/-0.003
0.01	182	\boxtimes	YES	+/-0.003
0.035	12	\oplus^B	YES	+/-0.003
0.065	10	\diamond	YES	+/-0.003
0.07	2	\times	NO	+/-0.003
0.095	14	\square	YES	+/-0.003
0.187	4	\oplus	YES	+/-0.003
0.215	12	\boxtimes	YES	+/-0.003

REVISION HISTORY


ECO	REV	DESCRIPTION	APP. ENG.	DATE
-	2	PRODUCTION	DB	05-14-19

LAYER STRUCTURE



NOTES: UNLESS OTHERWISE SPECIFIED

- FAB PER IPC-A-600.
- MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.
-FINISHED THICKNESS TO BE 0.062 +/- .005
-TOTAL OF 4 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.
-FLAMMABILITY RATING: 94 V-0 MINIMUM.
- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0/0 ARE PRIMARY DATUMS.
- DRILLING: -DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001 THICK MIN.
-ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
-HOLE LOCATION TOLERANCES ARE +/-0.003 IN RELATION TO CENTER
- FINISH: -SMOBC USING LPI BOTH SIDES, COLOR GREEN.
-GOLD IMMERSION BOTH SIDES.
-FOR SILKSCREENS: USE WHITE NON-CONDUCTIVE INK.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
- PCBS ARE TO BE RoHS COMPLIANT.
- SCORING FOR PANELIZED PCB:



- DESIGN HAS SOLDER MASK DEFINED PADS ON U1
WITH 0.029 PAD, 0.025 SOLDER MASK, AND 0.024 SOLDER PASTE.
DO NOT CHANGE ANY SIZE ON THIS COMPONENT.

UNLESS OTHERWISE SPECIFIED


DIMENSIONS ARE IN INCHES

TOLERANCES:

0.XX = ± 0.01

0.XXX = ± 0.005

INTERPRET DIM AND TOL
PER ASME Y14.5M-1994
THIRD ANGLE PROJECTION



APPROVALS

PCB DES. LT

APP ENG. DB

SCALE = NONE



TITLE: FABRICATION DRAWING

LOW EMI DUAL POSITIVE OUTPUT
μMODULE REGULATOR

SIZE N/A IC NO. LTM4655EY
DEMO CIRCUIT 2898A

REV
2

FILENAME: DC2898A-2.PCB

SHT 1 OF 1